




Stainless steel Bourdon tube pressure gauge type D3

benefits

- extremely compact design
- wetted parts and movement made of stainless steel
- Pressure connection welded to housing
- optional for control cabinet mounting
- tightness-tested with helium
- GOSSTANDART-certified

Application

For corrosive gaseous and liquid media which are not highly viscous and do not crystallise.

! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Type

D3

Nominal size

40

accuracy class (EN 837-1/6)

2.5

ranges (EN 837-1/5)

see ordering table

application area

static load: $\frac{3}{4}$ x full scale value

dynamic load: $\frac{2}{3}$ x full scale value

short-term: Full scale value

Operating temperature range

Medium: max. 100 °C

Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$

falling temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$

of full scale value

Degree of protection

IP 32 (EN 60529)

Connection

Stainless steel 316 L, centre back

Measuring element

Bourdon tube, Stainless steel 316 L

$\leq 60 \text{ bar}$: "C" type tube

$> 60 \text{ bar}$: helical tube

tightness-tested with helium

movement

Stainless steel

Dial

Aluminium, white
Scaling: black

Pointer

Aluminium, black

Housing

Stainless steel 304

window

Plastic, clipped in

Options

- 3-hole fixing, panel mounting bezel
- special scales
- other process connections
- oil- and grease-free version

Versions

Range	Mounting type	Type		Part number
0/1.6 bar	direct	RF40E D332	●	85011332
0/2.5 bar	direct	RF40E D332	●	85012332
0/4 bar	direct	RF40E D332	●	85013332
0/6 bar	direct	RF40E D332	●	85014332
0/10 bar	direct	RF40E D332	●	85015332
0/16 bar	direct	RF40E D332	●	85016332
0/25 bar	direct	RF40E D332	●	85017332
0/40 bar	direct	RF40E D332	●	85018332
0/60 bar	direct	RF40E D332	●	85019332
0/100 bar	direct	RF40E D332	●	85020332
0/160 bar	direct	RF40E D332	●	85021332
0/250 bar	direct	RF40E D332	●	85022332
0/400 bar	direct	RF40E D332	●	85023332
0/600 bar	direct	RF40E D332	●	85024332

- in-stock items
- Non-stock items