



ultrasonic level indicator

benefits

- non-contact level measurement
- easy adjustment even without medium
- robust housing for rough ambient conditions
- Suppression of interference signals
- Optional Ex version

Application

For continuous, non-contact level measurement in open or closed containers, tanks or silos. Suitable for liquid, mushy and pasty media. Ideal for sludge, adhesives, resins and waste water. The device can be easily adjusted even without a medium by means of the programming display with user-friendly menus. It also serves as a local display.

Description

The SonarFox® UST 20 level indicator uses the physical properties of ultrasonic waves to determine the level. An ultrasonic wave is emitted which is reflected by objects in the sound cone. The time up to the reception of the reflected echo is a measure of the distance. Since the mounting position is defined, it is possible to calculate the filling level of the medium. Type, density and temperature of the medium have no effect on the measurement – the only prerequisite is a reflecting surface. Acoustically diffuse surfaces such as foam or uneven surfaces of bulk solids are to be tested with regard to the application. An optional, additional alignment horn adapter can be used for such media. Installations or stirrers above the surface of the medium can be masked during empty setup.

Technical Specifications

Measuring accuracy

± 0.15 % FS

Temperature error

max. 0.04 %/K

Measuring interval

0–4 s

Operating temperature range

at process connection up to 90 °C (short-term up to 60 minutes)

Process pressure

max. 1 bar

Supply voltage

DC 18 – 36 V

Output signal

4–20 mA/HART, 2-wire

Load

$R_{\max} = 270 \, \Omega$ at $U = 24 \, \text{V}$

$R_{\max} = 180 \, \Omega$ at $U = 22 \, \text{V}$

$R_{\max} = 90 \, \Omega$ at $U = 20 \, \text{V}$

$R_{\max} = 45 \, \Omega$ at $U = 19 \, \text{V}$

Current input

max. 22 mA

Signal damping

adjustable from 0 to 99 s

Options

- Output RS-485 Modbus RTU
- Ex version

Housing

aluminium die cast

Ultrasonic transducer

PVDF

Degree of protection

IP 67 (EN 60529)

Electrical connection

Cable gland M16 x 1.5

Options

- Output RS-485 Modbus RTU
- Ex version

Versions

			Part no.
ultrasonic level indicator SonarFox® UST 20-01O01	measuring range 0.15/2 m, G1B	●	33545
ultrasonic level indicator SonarFox® UST 20-11O01	measuring range 0.25/6 m, G1½B	●	33544
ultrasonic level indicator SonarFox® UST 20-21O01	measuring range 0.4/10 m, G2¼B	●	33559
ultrasonic level indicator SonarFox® UST 20-31O01	measuring range 0.5/20 m, flange DN 100	●	33560
ultrasonic level indicator SonarFox® UST 20-01D01	measuring range 0.15/2 m, G1B, with display	●	33543
ultrasonic level indicator SonarFox® UST 20-11D01	measuring range 0.25/6 m, G1½B, with display	●	33542
ultrasonic level indicator SonarFox® UST 20-21D01	measuring range 0.4/10 m, G2¼B, with display	●	33557
ultrasonic level indicator SonarFox® UST 20-31D01	measuring range 0.5/20 m, flange DN 100, with display	●	33558

- in-stock items
- Non-stock items