



## Bourdon tube pressure gauge RF50GT

Part no. 85062301GT

Standard Bourdon tube pressure gauges for gas applications Type D3

### benefits

- Version safety pressure gauge S2 as per EN 837-1
- dual scale for measurement of different media (option)
- rear blow-out
- many customised versions available

### Application

For gaseous and liquid media which are not highly viscous and do not crystallise. Specially designed for gas technology devices, fittings and installations.

! For measuring gas or vapour, these gauges must be used in accordance with the table "Selection Criteria as per EN 837-2" (see appendix)!

### Technical Specifications

**Type**  
D3

**Nominal size**  
50

**Version**  
EN 837-1-S2

**accuracy class (EN 837-1/6)**  
1.6

**ranges (EN 837-1/5)**  
see ordering table

**application area**  
static load:  $\frac{3}{4}$  x full scale value  
dynamic load:  $\frac{2}{3}$  x full scale value  
short-term: Full scale value

### Operating temperature range

Medium: max. 60 °C  
Ambient: -20/+60 °C

### Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:  
at rising temperature approx.  $\pm 0.4$  %/10 K  
falling temperature approx.  $\pm 0.4$  %/10 K  
of full scale value

### Degree of protection

IP 32 (EN 60529)

### Connection

D301  
Brass  
bottom

**Measuring element**

Bourdon tube  
D301  
Copper alloy  
≤ 40 bar: "C" type tube  
> 40 bar: helical tube

**movement**

Brass

**Dial**

Aluminium, white  
Scaling: black

**Options**

- wetted parts stainless steel
- wetted parts oil-free and grease-free
- Helium leak test
- throttle screw
- special scales
- other connection threads

**Pointer**

Aluminium, black

**Housing**

Stainless steel 304, with rear blow-out

**window**

Plastic, snapped in

**Technical Drawings**

**Bottom connection**



**Dimensions (mm)**

| NG | a    | b    | Øc | c1 | c2 | G     | h  | s   | SW |
|----|------|------|----|----|----|-------|----|-----|----|
| 40 | 8,2  | 23,5 | 4  | 2  | 10 | G1/8B | 36 | 3   | 12 |
| 50 | 10,5 | 29   | 5  | 2  | 13 | G1/4B | 46 | 3,8 | 14 |
| 63 | 11   | 29,5 | 5  | 2  | 13 | G1/4B | 53 | 3,7 | 14 |

## Versions

| Range     | Mounting type | Type           |                       | Part number |
|-----------|---------------|----------------|-----------------------|-------------|
| 0/2.5 bar | direct        | RF50GT<br>D301 | <input type="radio"/> | 85062301GT  |

- in-stock items
- Non-stock items