

## diaphragm safety valve MS - heating systems MS Rp1 x Rp1¼

Part no. 42383

diaphragm safety valve MS - heating systems



### benefits

- for protection against overpressure in heating systems
- for water, water/glycol mixtures, liquids of fluid groups 1 and 2
- MSM with pressure gauge for indication of the system pressure

### Application

For sealed heating systems as per TRD 721; VdTÜV sheet Safety Valve 100 and 100/4 sheet 1; EN 12828. Also for water heating systems as per DIN 4751-2 with flow temperatures up to 120 °C and DIN 4751-3 with flow temperatures up to 95 °C. Suitable for water, water/glycol mixtures (with up to 50 % glycol).

### Description

Safety valve with factory-adjusted opening pressure. MSM with pressure gauge for indicating the system pressure. The size of the valve inlet determines the unit type, the outlet is ¼" larger.

### Technical Specifications

#### Connection

Rp1 x Rp1¼

#### Operating temperature range

Medium: -20/+120 °C

#### opening pressure

2.5 bar

#### Dimensions (W x H x D)

MS Rp1 x Rp1¼

#### Material

Housing: Brass

cap: PA 6, Red

#### type approval mark

TÜV.SV.yy-2017.13.H

"yy" represents the year of the approval

**Versions**

	maximum heating capacity	opening pressure	Pressure gauges	Part no.
diaphragm safety valve MS - heating systems MS Rp1 x Rp1¼	200 kW	2.5 bar	●	42383

- in-stock items
- Non-stock items