



Boiler manifold KSV 125-4 70 kW

Part no. 77312

Boiler manifold KSV 125 for heating pump assemblies PrimoTherm®

benefits

- compact and robust version in form-fit insulation
- for two or three heating pump assemblies, with optional hydraulic separator
- 2 wall mounting bracket for easy mounting included
- AFRISO boiler manifolds are tightness-tested in the factory.

Application

For distribution of the heating circuit water in sealed heating systems as per EN 12828 from the boiler to the heating pump assemblies PrimoTherm®.

Description

Boiler manifold as combination flow and return manifold for two, three, four or five heating pump assemblies. AFRISO boiler manifolds are tightness-tested in the factory; they are maintenance-free.

Technical Specifications

system connections

70 kW
 threaded socket G1½ male
 70 kW
 union nut G1½, flat-sealing

Axis distance

125 mm

Operating temperature range

Medium: max. 110 °C

Flow

70 kW
 3 m³/h

System pressure

max. 6 bar


Heat insulation



Polypropylene EPP

Scope of delivery

- Boiler manifold
- 2 x wall mounting bracket
- Insulation

Versions

	Heating circuits	hydraulic separator		Part no.
Boiler manifold KSV 125-4 70 kW	4	0		77312

-  in-stock items
-  Non-stock items