

Borealis wall

DESCRIPTION: Wall **TEXTURE:** Wood

PALLET OVERVIEW

	A
_	





NOTES

* For an authentic look, each color option is composed of a variety of darker & lighter tones. Natural ingredients such as granite are present within the recipe to allow for a range in tones, veining and textures from one stone to another.


The dimensional tolerance for Stonedge wet cast retaining wall units is: $\pm\,^3/_{16}"$ (5 mm) for height and $\pm\,^1\!/_2"$ (13 mm) for length and width. During the installation, the level between adjacent wall units will vary (usually more than for a dry cast wall unit) in order to obtain a more realistic appearance of a natural stone wall.

See page 97 to 118 for more technical information.

Specifications per pallet	Imperial	Metric
Cubing	32 ft ²	2.97 m ²
Linear coverage per pallet	64 lin. ft	19.51 lin. m
Weight	3 042 lbs	1 380 kg
Number of rows	4	
Coverage per row	8 ft²	0.74 m ²
Coverage per unit	2 ft ²	0.19 m ²
Linear coverage per unit	4 lin. ft	1.22 lin. m



imensions	in	mm	Units/pallet
Height	6	152	16 units
Depth	8	203	
Length	48	1 219	



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Visit our werbsite for more patterns.



