

<b>Factory model</b>	<b>TAC-12CHPB/RPV</b>
Code	
Power supply (V-Ph-Hz)	220-240V/50Hz
	0.5 L
Cooling Test Condition	35/24
Cooling Capacity(W)	3100
Cooling Input Power(W)	1100
Cooling Input Current(A)	4,8
EER (W/W)	2,8
Suitable area(m2)	/
Heat pump / Elecment	Heat pump
Heating Test Condition	20/12
Heating Capacity(W)	2640
Heating Input Power(W)	980
Heating Input Current(A)	4,2
COP (W/W)	2,7
Rated Power(W)	1250
Rated Current(A)	6,4
UL Rated Current (A)	/
Indoor air flow (Hi/Med/Lo) (m3/h)	330/250
Moisture Removal(L/h) Cooling	1,5
Sound (Hi/Lo)(dB(A))	
Sound Power	63
Refrigerant type	R290
Charge (g)	190
GWP	3
CO2	0,0006
Suction Pressure(Mpa)	1,2
Discharge Pressure(Mpa)	2,3
Net weight (kg)	26,2
Body demention (mm)	340*340*695
Gross weight 3A package (kg)	30,6
Packing demention (mm) 3A	398*371*895
Stuffing Quantity(20'/40'/40'HQ)	176/360/536