

NS2 Galvanized Iron Cleaner

Effective cleaner and degreaser

Duram NS2 Galvanized Iron Cleaner is an effective cleaner and degreaser for new and weathered galvanized iron, mild steel and other metals.


**ENGINEERED
FOR
METAL**


PRODUCT USES

- Effective cleaner and degreaser – removes surface oxidation (white rust), oils, grease, dirt and impurities.
- Removes temporary protective coating on new galvanized iron to allow paint adhesion.
- New or weathered galvanized iron, mild steel, aluminum and chromadek.
- Interior and exterior use.



ADVANTAGES

- Cleans and etches in one step.
- Removes surface oxidation, oils and grease.
- Etches surfaces for maximum adhesion.
- Ready to use.
- Water rinse and clean up.



APPLICATION

- Stir *Duram Duram NS2 Galvanized Iron Cleaner* well using a flat paddle, or shake container well.
- Thinning is not recommended.
- Wear protective gloves.
- Apply liberally to surface with a bristle brush in workable areas. Leave this product in contact with the surface for at least one minute, but do not allow to dry on the surface. Ensure there are no missed patches.
- Rinse thoroughly with water and a bristle brush or abrasive pad to remove all residue and to achieve a water break-free surface. Repeat procedure if necessary.
- Allow to dry.
- Ensure the appropriate Duram primer or undercoat is used.



CLEANING

- Water Clean up.



IMPORTANT

- Call our Technical Helpline or visit duram.co.za for queries and updated Datasheets and Material Safety Datasheets.
- Take care when lifting and carrying. In transit, keep tightly closed in a secure upright position.
- Whilst every care is taken in manufacture, no warranty is given relating to use.
- Do not mix with Mineral Turpentine.
- Observe special precautions in aggressive environments such as coastal and industrial areas.
- Do not apply outside if rain is expected. Apply when ambient and surface temperatures are 5°C to 35°C.
- Keep cool and protect against freezing.

- Donate unwanted paint. Dispose contents responsibly - do not empty into drains or watercourses. Recycle empty container.



SAFETY PRECAUTIONS

- Keep out of reach of children.
- Wear protective gloves and clothing.
- If swallowed: Immediately call a poison centre / doctor.
- If on skin: Wash with plenty of soap and water.
- Use in a well ventilated area. If experiencing respiratory symptoms: Move person to fresh air. Call a doctor.
- If in eyes: Rinse with water.



YOU MAY ALSO NEED

- 220 Grit Water Paper
- Primers and Undercoats
- Anti-fungal wash
- High Pressure Cleaner
- Paper towel and cloths
- Wire brush or sandpaper
- Masking tape
- Tape measure and stanley blade
- Drop sheets
- Ladder
- Paint scraper
- Screwdriver or paint can opener
- Flat paddle
- Protective gloves/protective clothing/eye protection/face protection
- Paint tray lined with foil to save clean-up time
- Additional utensils/products may be required in the preparation of surfaces.



TECHNICAL DATA

Pack size	1 litre, 5 litre	Physical state	Liquid
No of components	1	Density	1,0804g/cm ³
Colour	Clear		

Technical details above are provided in good faith. We believe in the quality of our products and will willingly replace any product in the unlikely event of a quality related performance failure. Whilst we are confident in guaranteeing the quality of our products, we cannot however accept any liability for performance failure due to the incorrect application of our products. Correct application is critical to the successful performance of our products and as this process falls outside of our control we are unable to cover the application under our product performance warranty. Where there are doubts, it is recommended that the user conduct their own suitability tests before use. To retain sheen and colour consistency of your paint, always make sure that the batch numbers are the same on all paint containers that you purchase.

Updated: June 2021 (this supersedes all previous publications)