

Dehumidifier

LEF 91 S

Reliable and efficient

Article number ▼

6262091

Brand ▼

Unicraft

Availability ▼

No stock available

Information:

Next availability

Expected on calendar week 21/2024

Catalog directory ▼

Workshop and lifting technology » Fans and dehumidifiers » Dehumidifiers

Purchase ▼

Minimum 8 pc(s).




Delivery content ▼

- Condensate drain hose 5 m

Shipping informations ▼

Packaging Metrics		Weights		Delivery		Other	
Length	570 mm	Gross	43 kg	Delivery	Carrier	DualUse	✗
Width	500 mm	Net	41 kg	Content	8 pc(s).	SCIP	n/a
Height	840 mm					SVHC	No

Root data ▼

Country of origin	EAN	Custom number	Quantity unit
 China	4036351316848	84158300	pc(s).

Description ▼

- Suitable for drying buildings and damp rooms, e.g. after water damage or on construction sites
- To prevent condensation and mold growth
- Mobile, impact-resistant housing for long durability
- Equipped with temperature control, defrost control, self-monitoring system, automatic hygrostat control and environmentally friendly refrigerant R290
- Control unit equipped with Smart Touch buttons, drain indicator and operating hours counter
- With removable and washable filters for use in dusty rooms
- High performance with low power consumption
- Low noise level
- With practical cable holder
- Integrated condensate pump for pumping out condensation water via the drain hose

Media informations ▼



Folding bar for space-saving storage




Control unit equipped with Smart-Touch buttons, countdown display and operating hours counter

Technical data ▼

General Features			
Max. air flow	850 m³/h	Air speed	12.6 m/s
Refrigerant	R290	Operating temperature	1 – 36 °C
Dehumidification power (30°C / 80 % RH)	90 l/d		
Dimensions and weights			
Outlet dimensions	317 x 280 mm	Diameter intake	150 mm
Length (product) approx.	555 mm	Width/depth (product) approx.	480 mm
Impeller diameter	170 mm	Height (product) approx.	820 mm
Net weight approx.	41 kg	Connection cable length	4,5 m
Electrical Data			
Absorbed power drive motor	0,96 kW	Delivery power	0,85 kW
Supply voltage	230 V	Duty type drive motor	S1
Mains frequency	50 Hz	Motor speed	1350 min ⁻¹
Total current draw	4.3 A	Engine efficiency	88 %
Noise emission			
Noise level	48 dB(A)		

Accessories ▼




Filter mat
LEF 70S/71S/9S0/91S

Article number ▼
6263070

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.

© 2024 Stürmer Maschinen GmbH

Page 3 of 3

April 11, 2024