

MainStreet™

Vinyl Siding

General Description: MainStreet™ siding is appropriate for use in new construction for single family homes, multi-housing projects and light commercial developments. MainStreet is also an ideal product for remodeling.

Styles:

Profile	Finish	Panel Projection	Wall Thickness (Nominal)	Lock Design	Colors	Accessory Pocket
Double 4" Clapboard	Woodgrain	9/16"	.042"	Post-formed	25	5/8" or 3/4"
Double 4" Dutchlap	Woodgrain	9/16"	.042"	Post-formed	25	1/2", 5/8" or 3/4"
Double 5" Clapboard	Woodgrain	9/16"	.042"	Post-formed	25	5/8" or 3/4"
Double 5" Dutchlap	Woodgrain	9/16"	.042"	Post-formed	25	5/8" or 3/4"
Triple 3" Clapboard	Smooth Brushed	9/16"	.042"	Post-formed	9	5/8" or 3/4"
Single 6-1/2" Beaded	Smooth Brushed	9/16"	.042"	Post-formed	8	5/8" or 3/4"
Single 8" Clapboard	Woodgrain	5/8"	.042"	Post-formed	1	3/4"

Colors: MainStreet siding profiles are available in a wide selection of colors. All colors are Spectrophotometer controlled and utilize exclusive Permacolor™ color science.

Colonial White (01)	Wedgewood Blue (89)*	Sterling Gray (33)	Natural Clay (60)	Forest (47)*
Autumn Yellow (10)*	Sandstone Beige (15)	Weathered Wood (90)*	Oxford Blue (32)	Hearthstone (19)*
Desert Tan (07)	Savannah Wicker (59)	Castle Stone (37)*	Autumn Red (23)*	Pacific Blue (27)*
Heritage Cream (11)	Seagrass (30)*	Cypress (42)*	Charcoal Gray (46)*	Sable Brown (29)*
Herringbone (04)*	Snow (31)	Granite Gray (34)*	Flagstone (97)*	Spruce (16)*

**Not available in T3" profile*

STUDfinder™: The patented STUDfinder Installation System combines precisely engineered nail slot locations with graphics. Nail slots are positioned 16" on center to allow for alignment with studs. STUDfinder graphics centered at each slot provide a quick and easy guide to help locate studs.

RigidForm™: MainStreet RigidForm 170 double nail hem technology stiffens siding for a straighter-on-the-wall appearance and provides wind load performance.

Lock: MainStreet's exclusive DuraLock™ is a substantially larger lock than is found on competing products, with a rigid teardrop shape and engineered angular locking leg for a positive, snap fit application and exceptional wind resistance.

Accessories: CertainTeed manufactures a wide range of siding accessories which are compatible with MainStreet siding styles and colors. Accessory products include installation components, soffit, window and door trim, corner lineals, corner systems and decorative moldings.

Composition: MainStreet siding products are produced using PVC resin.

Technical Data: MainStreet siding is in compliance with ASTM specification for Rigid Polyvinyl Chloride (PVC) Siding D3679, and the requirements of the 2015, 2018, 2021 and 2024 International Residential Code and International Building Code, the 2020 and 2023 Florida Residential Code and Florida Building Code, and the 2019 and 2022 California Residential Code and California Building Code, and the 2020 National Building Code of Canada. MainStreet siding meets

or exceeds the properties noted in Table 1.

Table 1

ASTM E 84	Meets Class A flame spread requirements as tested according to ASTM E84.
ASTM D 635	Material is self-extinguishing with no measurable extent of burn when tested in accordance with this specification.
NFPA 268	Radiant Heat Test - Ignition Resistance of Exterior Walls - Conclusion that CertainTeed met the conditions for allowable use as specified in section 1406 of the International Building Code.

Important Fire Safety Information: When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt or burn, and may thereby expose material underneath. Care must be exercised when selecting underlayment materials because many underlayment materials are made from organic materials that are combustible. You should ascertain the fire properties of underlayment materials prior to installation. All materials should be installed in accordance with local, state and federal Building Code and fire regulations.

Wind Load Testing: CertainTeed MainStreet siding has been tested per ASTM D 5206 standard test method for wind load resistance to withstand negative wind load pressures and their mph equivalents as shown in the chart below. All products exceed industry standards for wind load performance. Check with your local building inspector for wind load requirements in your area for the type of structure you are building.

Table 2

Product	Fastener Spacing	2015/2018 IBC/IRC			2021/2024 IBC/IRC		
		Standard Design Pressure Rating	Maximum Windspeed (mph)		Standard Design Pressure Rating	Maximum Windspeed (mph)	
			ASD	ULT		ASD	ULT
Double 4" Clapboard	Nails 16" o.c.	105.0	209	270	76.0	177	229
Double 5" Clapboard	Nails 16" o.c.	89.4	193	249	64.0	164	211
Double 4" Dutchlap	Nails 16" o.c.	89.4	193	249	64.0	164	211
Double 5" Dutchlap	Nails 16" o.c.	83.8	186	240	60.0	158	204
Triple 3" Clapboard	Nails 16" o.c.	89.4	193	249	64.0	164	211
Single 6-1/2" Beaded	Nails 16" o.c.	89.4	193	249	64.0	164	211
Single 8" Clapboard	Nails 16" o.c.	89.4	193	249	64.0	164	211

* Windload calculations based on ASTM D3679, ASCE 7-10, 30ft High, Exposure B

Documents: CertainTeed Vinyl Siding meets the requirements of one or more of the following specifications.

- VSI/Intertek PCL-0504
- Texas Department of Insurance Product Evaluation EC-11
- Conforms to ASTM Specification D3679
- ICC-ES Evaluation Report ESR-1066
- ICC-ES Evaluation Listing ESL-1462 (Canada)
- Florida BCIS Approval FL1573 & FL12483
- For specific product evaluation/approval information, call 800-233-8990.


Installation: Prior to commencing work, verify governing dimensions of building, examine, clean and repair, if necessary, any adjoining work on which the siding is in any way dependent for its proper installation. Sheathing materials must have an acceptable working surface. Siding, soffit and accessories shall be installed in accordance with the latest editions of CertainTeed installation manuals on siding and soffit. Installation manuals are available from CertainTeed and its distributors.

Warranty: CertainTeed supports MainStreet siding products with a Lifetime Limited Warranty including PermaColor Lifetime Fade Protection to the original homeowner. The warranty is transferable if the home is sold.

Technical Services: CertainTeed maintains an Architectural Services staff to assist building professionals with questions regarding CertainTeed siding products. Call 800-233-8990 for samples and answers to technical or installation questions.

Sample Short Form Specification: Siding as shown on drawings or specified herein shall be MainStreet™ Vinyl Siding as manufactured by CertainTeed LLC, Malvern, PA. The siding shall have a .042" nominal thickness. Installation shall be in accordance with manufacturer's instructions.

Three-part Format Specifications: Long form specifications in three-part format are available from CertainTeed by calling our Architectural Services Staff at 800-233-8990. These specifications are also available on our website at certainteed.com.



CertainTeed LLC
20 Moores Road
Malvern, PA 19355
certainteed.com
© 01/24