

SECTION 1: IDENTIFICATION

Manufacturer

Choice Adhesives

Address

 666 Redna Terrace, Suite 600
Cincinnati, OH 45215

 2500 Carroll Avenue
Lynchburg, VA 24501

Information Telephone Number

513-772-1234

434-847-5671

Emergency Contact Number:

800-424-9300 (CHEMTREC)

Recommended Use

Adhesive

SECTION 2: HAZARD(S) IDENTIFICATION

Classifications

Skin Irritation: Category 2
 Eye Damage: Category 2A
 Reproductive Toxicity: Category 2
 STOT Single Exposure: Category 3
 STOT Repeated Exposure: Category 2
 Aspiration: Category 1
 Flammable Liquid: Category 2
 Aquatic Hazard Acute: Category 1
 Aquatic Hazard Long-term: Category 1

Pictograms

GHS Signal Word

DANGER!

Hazard Statements

Causes skin irritation.
 Causes serious eye irritation.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.
 Highly flammable liquid and vapor.
 Very toxic to aquatic life.
 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking. Keep cool.
 Ground and bond container and receiving equipment.

IF ON SKIN: Take off all contaminated clothing and rinse skin with water.
 Avoid release to the environment. Collect spillage.
 Avoid breathing vapors. Use in a well-ventilated area.
 IF INHALED: Call a doctor if you feel unwell. Remove person to fresh air and keep comfortable for breathing.
 Do not breathe vapors. Get medical attention if you feel unwell.
 IF SWALLOWED: Call a doctor if you feel unwell. Do NOT induce vomiting.
 IF ON SKIN: Take off contaminated clothing and wash before reuse. Wash skin with plenty of water. If skin irritation occurs: Get medical attention.

Potential Health Effects

Principal Routes of Exposure

Inhalation, skin absorption, eye contact

Acute Effects

Eye:	Contact with eyes may cause irritation. Direct contact with liquid or vapors may cause stinging, tearing, redness, swelling and eye damage.
Skin:	May cause skin irritation and/or dermatitis. Prolonged or repeated contact or exposure to vapors may cause redness, burning, and drying and cracking of skin.
Inhalation:	Breathing high concentrations of vapors may cause irritation of the nose and throat or signs of nervous system depression (e.g., headache, nausea, drowsiness, dizziness, vomiting, loss of coordination and fatigue)
Ingestion:	Ingestion may cause irritation of the digestive tract, nausea, vomiting, and signs of nervous system depression

Chronic Effects

Avoid repeated exposure. May cause blood damage. Repeated contact may cause allergic reactions in very susceptible persons.

Aggravated Medical Conditions

Pre-existing eye, skin or respiratory disorders may be aggravated by exposure to this product.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Designation
CAS No.
% by Weight

Acetone	67-64-1	22 - 40%
Hexane	110-54-3	22 - 40%
Heptane	142-82-5	5 - 15%
Toluene	108-88-3	5 - 15%

Any remaining ingredients (to comprise 100% of the product) should be considered a proprietary blend of non-hazardous substances, or materials below threshold reporting limits.

SECTION 4: FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance

Eyes

Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for

Skin	thorough irrigation. If irritation persists, get immediate medical attention.
Inhalation	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash affected areas thoroughly with mild soap. If skin irritation persists, get immediate medical attention.
Ingestion	Move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen and get immediate medical attention.
Ingestion	Do not induce vomiting seek immediate medical attention. If vomiting occurs, keep head lower than hips to prevent aspiration.
Notes to Physician	Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media	Carbon dioxide, dry chemicals, foam. Water may be helpful in keeping adjacent containers cool; avoid spreading the liquid with water used for cooling. Water-based sprinkler systems may help contain larger fires.
Special Protective Equipment and firefighting procedures	Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific hazards arising from the chemical	Closed containers may rupture if exposed to fire or extreme heat. May produce toxic fumes if burning.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Methods for Clean-up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.
Other Information	None known.

SECTION 7: HANDLING & STORAGE

Handling	Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from extremes of heat or cold. Keep in properly labeled containers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Note: Any items listed in the above with workplace control parameters which are not listed in section 3 are below threshold reporting values.

REL - Recommended Exposure Limits

TLV - Threshold Limit Value

Exposure Limits

Components with workplace control parameters:

Hazardous Components	OSHA PEL	ACGIH TLV
Acetone	1000	250
Hexane	500	50
Heptane	500	400
Toluene	200	20

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eyes/Face

Safety goggles or glasses, or full face shield.

Skin

Protective gloves and impervious clothing. Consult the glove/clothing manufacturer for proper selection of materials.

Respiratory

In operations where exposure limits are exceeded, use a NIOSH-approved respirator that has been selected by a technically qualified person for the specific work conditions.

Hygiene Practices

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Red liquid.	Upper Flammability/Explosive Limit	9.22
Oxidizing Properties	No Data Available	Lower Flammability/Explosive Limit	1.66
Odor	Solvent odor.	Vapor Pressure mm Hg	Not available
Odor Threshold	No Data Available	Vapor Density	Heavier than air
pH Value	No Data Available	Bulk Density (lb/gal)	6.82
Melting Point / Freezing Point	No Data Available	VOC Content (g/L)	390
Boiling Point	133.0 °F [56.1 °C]	VOC Less Water & Exempts (g/L)	546
Non-Volatile (wt%)	24.74	Specific Gravity (g/l)	0.819
Flash Point	-20.0 °F [-28.9 °C]	Auto-Ignition Temperature	No Data Available
Explosive Properties	No Data Available	Decomposition Temperature	No Data Available
Evaporation Rate	Faster than nBuAc	Partition Coefficient	No Data Available

Flammability (solids)

No Data Available

Viscosity

No Data Available

Solubility in Water

Insoluble

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions. Hazardous polymerization does not occur.

Possibility of Hazardous Reactions

None under normal conditions of use.

Conditions to Avoid

Keep away from open flames, hot surfaces, static electricity and sources of ignition. Avoid extremes of heat or cold.

Materials to Avoid

Incompatible with strong acids and bases, alkali metals, halogens, and strong oxidizing agents.

Hazardous Decomposition

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide, smoke, and other unidentified organic compounds may be formed during combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

Numerical Measures of Toxicity for Individual Components
Likely Routes of Exposure

Inhalation, skin absorption, eye contact.

Acute Toxicity

Oral: No data; Skin: No data; Inhalation: No data

Sensitization

Respiratory: No data; Skin: No data

Irritation

Skin: Category 2

Mutagenicity

No data

Reproductive Toxicity

Category 2

Aspiration Hazards

Category 1

Specific Target Organ Toxicity - Single Exposure

Category 3

Specific Target Organ Toxicity - Repeated Exposure

Category 2

Chronic Toxicity / Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen. If no ingredients are listed below, then there are no known classifications.

Component
IARC
NTP
OSHA

SECTION 12: ECOLOGICAL INFORMATION

The information and data for components are listed individually for areas of ecological consideration below.

Aquatic Toxicity

Acute and prolonged toxicity to fish:

No Data Available

Acute toxicity to aquatic invertebrates:

No Data Available

Description:

FORMICA F-HSR+

Date Issued

Page 6 of 8
04/06/2020

Environmental fate and pathways:

No Data Available

Persistence and Degradability

No Data Available

Mobility in Soil

No Data Available

Bioaccumulative Potential

No Data Available

Other Adverse Effects

No Data Available

SECTION 13: DISPOSAL CONSIDERATION

Waste Disposal Method

Dispose of in accordance with all applicable local, state, and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

SECTION 14: TRANSPORT INFORMATION

The shipping classification in this section is meant as a guide to overall classification of the product. However, transportation classifications may be subject to change with changes in package size. Consult shipper requirements under 49 CFR, IATA and IMDG to assure regulatory compliance.

REGULATION

DESCRIPTION

DOT

Proper Shipping Name

ADHESIVES

Technical Name

Not available

Hazard Class

3

UN Number

UN1133

Packing Group

PGII

Placards



ICAO / IATA

No Data Available

IMDG / IMO

No Data Available

SECTION 15: REGULATORY INFORMATION

US TSCA	Yes All components are listed or exempt.
Canada DSL	Yes All components are listed or exempt.
OSHA Regulatory Status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
SARA 313	Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation	CAS Number	Weight %
Hexane	110-54-3	22 - 40%
Toluene	108-88-3	5 - 15%

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

Chemical Designation	CAS Number	Weight %
Hexane	110-54-3	22 - 40%
Toluene	108-88-3	5 - 15%

State Regulations

California Prop. 65

This product contains one or more chemicals known to the state of California to cause cancer and/or reproductive harm. Unless chemical names are listed below, these chemicals are present only in trace amounts. www.P65Warnings.ca.gov

Chemical Name	CAS Number
Hexane	110-54-3
Toluene	108-88-3
Ethylbenzene	100-41-4
Naphthalene	90-20-3

SECTION 16: OTHER INFORMATION

NFPA is a Health, Flammability and Reactivity rating: 230B

4 SEVERE HAZARD, 3 SERIOUS HAZARD, 2 MODERATE HAZARD, 1 SLIGHT HAZARD, 0 MINIMAL HAZARD, * Chronic Hazard



Safety Data Sheet

Description:

FORMICA F-HSR+

Date Issued

Page 8 of 8

04/06/2020

DISCLAIMER

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy his self that the product is entirely suitable for his purposes.

END OF SAFETY DATA SHEET
