



THE DRIVING FORCE IN THE FASTENER INDUSTRY

Dome Head With Cutting Ribbon

- Increased Pull-Through Resistance Due To Bigger Head Surface
- Saw Tooth Cutting Ribbon for Clean Finish Look

Case Hardened Steel

- Hardened Shell For High Performance In Tensile, Torque and Shear
- Softer Core for Flexibility and High Bending Angles

Reamer Thread

- Enlarges The Hole Created By The Screw For Easier Transition To The Upper Sleeve

CHROME 6 Free Coating

- Corrosion Resistance Coating
- Interior/Exterior Use
- Free Of Known Cancer-Causing Chemicals
- Compliant With Ground Contact Treated Lumber ACQ-D 0.6pcf

The Bulge

- Relieves The Friction On Minor Diameter Of Screw

L-Cutting Blades

- Saw Blade Style Cutting Edges
- Reducing Torque

Blade Cutting Thread

- Cuts A Smooth Path Into Natural Or Synthetic Materials
- Provides The Connection With A High Withdrawal Resistance


Angled Cut

- Chip Catching Groove
- Allows The Screw To Penetrate Materials Without Splitting *

Tapper Point with Cork Screw Start

- Allows Pin-Point Placement Of The Tip With Easy Start
- Full Thread Engagement With The First Turn

CAP SCREW™



Tight Star Recess

- Excellent Fit
- Wobble Free
- Optimal Force Transmission
- Zero Stripping
- Compatible With Regular Star Drive Bits