



 (\mathbf{c})



ZBOX & ZARGEN DRAWER SYSTEMS

ZBox and Zargen steel drawer systems provide the flexibility to handle the most demanding design needs with quick construction and simple installation.







Versatile. Reliable. Proven.

ZBox and Zargen drawer systems offer versatility in application and deliver superior performance with a tried-and-tested technology.

Innovative functional solutions.

For years the Zargen metal drawer system has provided cabinet makers the quality, functionality, and versatility expected of Grass hardware. From residential and office furniture to commercial and institutional settings, the Zargen System consistently delivers superior performance. Offering five side heights and flexible railing systems, the Zargen drawer provides endless possibilities for the well-organized storage system.

The Grass ZBox offers all the same features of the Zargen system but with one new twist – the Zargen drawer side is mounted to a Grass ball bearing slide to create a new full extension metal drawer. The combined strength of the ball bearing slides with the Zargen's steel construction offers a drawer solution that saves time and money with its quick drawer box construction and simple installation. The ZBox offers standard drawer and deep drawer heights, railing system, and Pendaflex filing systems to provide a wide range of possibilities for your cabinet construction.



ZBox & Zargen

Table of Content

Description	Adjustment	Page
ZBox Features and Benefits		6
ZBox Technical Information		8
 ZBox 6423 213mm (8 3/8") Side Height Integrated drawer slide and side Full Extension 	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	10
 ZBox 6223 149mm (5 7/8") Side Height Integrated drawer slide and side Full Extension 	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	12
 ZBox 6023 85mm (3 3/8") Side Height Integrated drawer slide and side Full Extension 	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	14
Zargen Features and Benefits		16
Zargen Technical Information		18
 Zargen 6436 213mm (8 3/8") Side Height Integrated drawer slide and side 	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	20
 Zargen 6236 149mm (5 7/8") Side Height Integrated drawer slide and side 	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	22
Zargen 6136 • 117mm (4 5/8") Side Height • Integrated drawer slide and side	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	24
Zargen 6036 • 85mm (3 3/8") Side Height • Integrated drawer slide and side	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	26
 Zargen 6026 85mm (3 3/8") Side Height Integrated drawer slide and side 	 Height adjustment ±2.0mm Side adjustment ±1.5mm 	28

ZBox & Zargen

Table of Content

Description	Adjustment	Page
 Zargen 6035 43mm (1 11/16") Side Height Integrated drawer slide and side 	 Height adjustment ±2.0mm via cam Side adjustment ±1.5mm 	30
 Zargen Soft-close Liquid damper for improved performance 	 Height adjustment ±2mm via elongated hole 	32
 6100 Railing System Railing System For use with all ZBox and Zargen drawers Allows end user to customize storage space 		34
 Pendaflex File Railing Three file systems available For use with all ZBox and Zargen drawers Easy installation 	 Accommodates letter and legal size folders 	35
Accessories and Assembly Aids		38
Machinery Grass PRO 1 Boring and insertion machine Functional design Easy maintenance ZRam For drawer assembly Activated by air For ZBox and Zargen assembly		42


Features and Benefits

ZBox

Features



- · Integrated side mount ball bearing drawer slide and metal drawer side
- Ball bearing telescopic full extension
- Hold-in detent ensures drawers stay closed
- · Easy lever disconnect for removal of drawer box from cabinet member
- Drawer side white epoxy finish; Drawer slide zinc coated steel
- Load capacity: 100 lb dynamic, 100 lb static
- Adjustments: Cam Height ±2mm, Side ±1.5mm
- Zargen is made in the USA, ZBox is assembled in the USA





Adjustment via integrated front fixing bracket Height adjustment ±2mm Side adjustment ±1.5mm

ZBox combines the performance of ball bearing smoothness with the strength and adjustability of the Zargen Drawer System. A combination backed by GRASS.

Features

- Frameless or face frame application
- Zargen side: white epoxy finish
- Ball bearing slide: zinc coated steel
- Continuous bearings ensure smooth running performance
- Manufactured from cold rolled steel
- Face frame rear mounting bracket available
- Meets and exceeds ANSI/BHMA A156.9 Standard, Grade 1
- Patented design





Technical Information

ZBox

Adjustment Features 6423, 6223


- Height Adjustment: Loosen screws 2 slightly.
 Adjust screw 1 (adjustment ±2mm). Tighten screws 2.
- Side Adjustment: Loosen screws 2 slightly.
 Adjust front to required position (adjustment range ±1.5mm).
 Tighten screws 2.

After adjusting front panel, mount fixing screw

Adjustment Features 6023

Height Adjustment: Loosen screws 2 slightly. Adjust screw 1 (adjustment ±2mm). Tighten screws 2.

Side Adjustment: Loosen screws 2 slightly.
 Adjust front to required position (adjustment range ±1.5mm).
 Tighten screws 2.



System Organization

A unique feature of the ZBox System is its universal adaptability to Zargen Accessories. The 6100 railing system offers function, drawer space utilization, and economy. Drawer with railing 6100



Weight Capacities per Pair of Slides




ZBox: 100 lb dynamic load rating, 100 lb static load rating

ZBox meets and exceeds the minimum requirements of ANSI/BHMA A156.9 Standard, Grade 1

Patented Design

Technical Information

ZBox




								-
Drewerlowsth	Screw Hole Locations		Face Frame		Frameless			
Drawer Length	Slide Travel			С	D	Min	Max	Min
350 (13 3/4")	350	128	224	-	-	365 (14 3/8")	406 (15 31/32")	364 (14 11/32")
400 (15 3/4")	400	128	224	320	-	415 (16 11/32")	453 (17 27/32")	414 (16 5/16")
470 (18 1/2")	450	128	224	352	-	476 (18 3/4")	503 (19 13/16")	475 (18 11/16")
510 (20 1/16")	500	128	224	352	416	516 (20 5/16")	553 (21 25/32")	515 (20 9/32")
550 (21 5/8")	550	128	224	352	416	565 (22 1/4")	603 (23 3/4")	564 (22 7/32")

Removing the Drawer



Pull out drawer to expose the release lever mechanism



Easy Release Lever: Right Side - push up; Left Side - push down Pull out the drawer



Remove drawer

ZBox 6423

213mm (8 3/8") Side Height




- · Integrated side mount ball bearing drawer slide and metal drawer side
- Ball bearing telescopic full extension
- Hold-in detent ensures drawers stay closed
- · Easy lever disconnect for removal of drawer box from cabinet member
- Drawer side white epoxy finish; Drawer slide zinc coated steel
- Load capacity: 100 lb dynamic, 100 lb static
- Adjustments: Cam Height ±2mm, Side ±1.5mm
- Zargen made in the USA, ZBox assembled in USA

ZBox 6423 Full Extension Slide, 100 lbs



Description	Drawer Length	Item No.	PU
ZBox 6423/350	350 (13 3/4")	30144-03	5
ZBox 6423/400	400 (15 3/4")	30145-03	5
ZBox 6423/470	470 (18 1/2")	30146-03	5
ZBox 6423/510	510 (20 1/16")	30147-03	5
ZBox 6423/550	550 (21 5/8")	30148-03	5




			Bottom Panel Length		
_	_	Drawer Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Extension
	panel	350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	350 (13 3/4")
	Back pa	400 (15 3/4")	381 (15")	378 (14 7/8")	400 (15 3/4")
	Ba	470 (18 1/2")	451 (173/4")	448 (175/8")	450 (17 3/4")
		510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	500 (19 11/16")
8"-3/4	!")	550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	550 (21 5/8")

Face Frame Brackets









PU - Packaging unit





Drawer Installation Measurements




For Face Frame Cabinetry Use:

Back

• Attach face frame rear mounting brackets (Item # 30200-09) to slide

Front - Setback=37mm


- Use Inset bracket (Item # 13901-37) or
- · Block out the face frame
- · See page 41 for installation instructions



1 Height Adjustment: Loosen screws 2 slightly Adjust screw 1 (adjustment ±2mm). Tighten screws 2.

2 Side Adjustment: Loosen screws 2 slightly. Adjust front to required position (adjustment range ±1.5mm). Tighten screws 2.

After adjusting front panel, mount fixing screw.



€

ZBox 6223

149mm (5 7/8") Side Height




- · Integrated side mount ball bearing drawer slide and metal drawer side
- Ball bearing telescopic full extension
- Hold-in detent ensures drawers stay closed
- · Easy lever disconnect for removal of drawer box from cabinet member
- Drawer side white epoxy finish; Drawer slide zinc coated steel
- Load capacity: 100 lb dynamic, 100 lb static
- Adjustments: Cam Height ±2mm, Side ±1.5mm
- Zargen made in the USA, ZBox assembled in USA

ZBox 6223 Full Extension Slide, 100 lbs



Description	Drawer Length	Item No.	PU
ZBox 6223/350	350 (13 3/4")	30139-03	5
ZBox 6223/400	400 (15 3/4")	30140-03	5
ZBox 6223/470	470 (18 1/2")	30141-03	5
ZBox 6223/510	510 (20 1/16")	30142-03	5
ZBox 6223/550	550 (21 5/8")	30143-03	5




			Bottom Panel Length		
_	_	Drawer Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Extension
	panel	350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	350 (13 3/4")
	Back pa	400 (15 3/4")	381 (15")	378 (14 7/8")	400 (15 3/4")
	Ba	470 (18 1/2")	451 (173/4")	448 (175/8")	450 (17 3/4")
		510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	500 (19 11/16")
- 3/4"	')	550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	550 (21 5/8")

Face Frame Brackets






Description	Drawer Length	Item No.	PU
Face frame rear mount bracket		30200-09	100
2 Inset bracket set*		13901-37	1
Inset bracket set*		13901-08	50
*See page 41 for installation instructions.			




PU - Packaging unit





Drawer Back and Bottom Measurements



Drawer Installation Measurements








ZBox 6023

85mm (3 3/8") Side Height




- · Integrated side mount ball bearing drawer slide and metal drawer side
- Ball bearing telescopic full extension
- Hold-in detent ensures drawers stay closed
- Easy lever disconnect for removal of drawer box from cabinet member
- Drawer side white epoxy finish; Drawer slide zinc coated steel
- Load capacity: 100 lb dynamic, 100 lb static
- Adjustments: Cam Height ±2mm, Side ±1.5mm
- Zargen made in the USA, ZBox assembled in USA

ZBox 6023 Full Extension Slide, 100 lbs



Description	Drawer Length	Item No.	PU
ZBox 6023/350	350 (13 3/4")	30134-03	5
ZBox 6023/400	400 (15 3/4")	30135-03	5
ZBox 6023/470	470 (18 1/2")	30136-03	5
ZBox 6023/510	510 (20 1/16")	30137-03	5
ZBox 6023/550	550 (21 5/8")	30138-03	5




	Drawer Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Extension
panel	350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	350 (13 3/4")
a ka	400 (15 3/4")	381 (15")	378 (14 7/8")	400 (15 3/4")
Back	470 (18 1/2")	451 (173/4")	448 (17 5/8")	450 (17 3/4")
1 	510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	500 (19 11/16")
/8" - 3/4")	550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	550 (21 5/8")

Bottom Panel Length

Face Frame Brackets









PU - Packaging unit





Drawer Back and Bottom Measurements



Drawer Installation Measurements








Features and Benefits

Zargen

Features



- Integrated drawer slide and drawer side
- White epoxy finish
- Load capacity: 100 lb dynamic, 100 lb static
- Installation width 15.5mm (5/8")
- Made in the USA




Versatile. Reliable. Proven. Zargen delivers superior performance with tried-and-tested technology.




Features

- Available in five drawer heights
 - 43mm (1 11/16")
 - 85mm (3 3/8")
 - 117mm (4 5/8")
 - 149mm (5 7/8")
 - 213mm (8 3/8")



Technical Information


Zargen



The double stop prevents the drawer from falling out while being extended. In addition, the drawer can be locked in the open position. Special rollers provide lateral stability and a smooth glide. The rollers are tested for durability, and washers behind the rollers ensure stability.

The integrated drawer stop protects the drawer front from impact during closing. Furthermore, it acts as a shock absorber and a self-alignment feature for the drawer fronts.

Closing



Self-Closing From a range of 60mm (2 3/8") out, the drawer closes quietly and smoothly. Drawers closed with force will not bounce back.

Minimum Reveal Minimum reveals are required between fronts due to the specifically formed closing action.

Parallel Closing The parallel closing action keeps the drawer front properly aligned with the cabinet front. Cabinet members feature elongated holes for height adjustment.


Adjustment Features 6036, 6035

Height Adjustment:

Loosen screws 2 slightly. Adjust screw 1 (adjustment ±2mm). Tighten screws 2.

Side Adjustment:

Loosen screws 2 slightly. Adjust front to required position (adjustment range ± 1.5 mm). Tighten screws 2.



Adjustment Features 6436, 6236, 6136

Height Adjustment:

Loosen screws 2 slightly. Adjust screw 1 (adjustment ±2mm). Tighten screws 2.

Side Adjustment:

Loosen screws 2 slightly. Adjust front to required position (adjustment range ± 1.5 mm). Tighten screws 2.

After adjusting front panel, mount fixing screw

Fixing Screw 2 1 2


Weight Capacities per Pair of Slides


Zargen: 100 lb dynamic load rating; 100 lb static load rating

Zargen meets and exceeds the minimum requirements of ANSI/BHMA A156.9 Standard, Grade 1




Cabinet Member






To simplify installation of the cabinet member, a unique double-hole pattern for 32mm and 37mm setback has been developed.

Installation



With Euro Screws


(Flat Head Phillips) the cabinet member can be fastened into a pre-drilled 32mm hole system. See cabinet member drawing to the left for all fastening positions.



With Wood Screws

(#6x5/8" Flat Head Phillips) the cabinet member is screwed directly on the end panel. To guarantee precise positioning, precenter with a Grass pilot drill. For wood screws, use the front section of the double hole.


Captive Rollers



Manufacturing often is accompanied by tolerance problems. To avoid this situation, Grass slides are designed to eliminate side movement of the drawer. After installation, the right drawer member blends perfectly with the right cabinet member for guidance; the left side allows for cutting tolerance of the drawer and the cabinet components.

System Organization

Slide with railing (6036, 6100)



A unique feature of the Zargen System is its universal adaptability in cabinetry. The system offers function, drawer space utilization and economy. With regular drawers, inset pull-outs, divider railings and more the Zargen System provides a variety of organizational solutions. Zargen 6436

213mm (8 3/8") Side Height




- Integrated drawer slide and drawer side
- Self-closing feature with 60mm (2 3/8") closing range
- Built-in drawer front bumpers
- Quick assembly through dowelled and integrated front fixing brackets
- White epoxy finish
- Tolerance adjustment 2mm (3/32")
- Load capacity: 100 lb
- Adjustments: Cam height (± 2mm), side (± 1.5mm)
- Made in the USA

Zargen 6436 slide, 100 lb (45 kg)




Drawer Extension

Description	Slide Length	Item No.	PU
Zargen 6436/350	350 (13 3/4")	22910-03	5
Zargen 6436/400	400 (15 3/4")	22911-03	5
Zargen 6436/440	440 (17 3/8")	22708-03	5
Zargen 6436/470	470 (18 1/2")	22709-03	5
Zargen 6436/510	510 (20 1/16")	22710-03	5
Zargen 6436/550	550 (21 5/8")	22711-03	5
Zargen 6436/510	510 (20 1/16")	22710-12	200
Zargen 6436/550	550 (21 5/8")	22711-12	200




	Bottom Panel Length		Extension		
Slide Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Single Stop	Double Stop	
350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	280 (11")	-	
400 (15 3/4")	381 (15")	378 (14 7/8")	300 (11 13/16")	314 (12 3/8")	
440 (17 3/8")	421 (16 9/16")	418 (16 7/16")	340 (13 3/8")	354 (13 15/16")	
470 (18 1/2")	451 (173/4")	448 (17 5/8")	370 (14 9/16")	384 (15 1/8")	
510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	410 (16 1/8")	424 (16 11/16")	
550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	450 (17 11/16")	464 (18 1/4")	




20




Drawer Back and Bottom Measurements



Drawer Installation Measurements





*Allow minimum of 3mm (1/8") for bottom clearance. If screws are used, increase clearance accordingly.

Drawer slide attachment:

Wood screws #6 x 5/8 FHP Euro screw lengths 18mm, 13mm, 7.5mm

Bottom panel thickness: 12.7 - 19mm (1/2" - 3/4") Back panel thickness: 16 - 19mm (5/8" - 3/4") Back panel height: min 210mm (8 1/4") Zargen 6236

149mm (5 7/8") Side Height




- Integrated drawer slide and drawer side
- Self-closing feature with 60mm (2 3/8") closing range
- Built-in drawer front bumpers
- Quick assembly through dowelled and integrated front fixing brackets
- White epoxy finish
- Tolerance adjustment 2mm (3/32")
- Load capacity: 100 lb
- Adjustments: Cam height (± 2mm), side (± 1.5mm)
- Made in the USA

Zargen 6236 slide, 100 lb (45 kg)




Description	Slide Length	Item No.	PU
Zargen 6236/350	350 (13 3/4")	22908-03	5
Zargen 6236/400	400 (15 3/4")	22909-03	5
Zargen 6236/440	440 (17 3/8")	22704-03	5
Zargen 6236/470	470 (18 1/2")	22705-03	5
Zargen 6236/510	510 (20 1/16")	22706-03	5
Zargen 6236/550	550 (21 5/8")	22707-03	5
Zargen 6236/350	350 (13 3/4")	22908-12	200
Zargen 6236/400	400 (15 3/4")	22909-12	200
Zargen 6236/440	440 (17 3/8")	22704-12	200
Zargen 6236/470	470 (18 1/2")	22705-12	200
Zargen 6236/510	510 (20 1/16")	22706-12	200
Zargen 6236/550	550 (21 5/8")	22707-12	200



Drawer Extension


	Bottom Panel Length		Exter	nsion
Slide Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Single Stop	Double Stop
350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	280 (11")	-
400 (15 3/4")	381 (15")	378 (14 7/8")	300 (11 13/16")	314 (12 3/8")
440 (17 3/8")	421 (16 9/16")	418 (16 7/16")	340 (13 3/8")	354 (13 15/16")
470 (18 1/2")	451 (173/4")	448 (17 5/8")	370 (14 9/16")	384 (15 1/8")
510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	410 (16 1/8")	424 (16 11/16")
550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	450 (17 11/16")	464 (18 1/4")









Drawer Back and Bottom Measurements



Drawer Installation Measurements





*Allow minimum of 3mm (1/8") for bottom clearance. If screws are used, increase clearance accordingly.

Drawer slide attachment:

Wood screws #6 x 5/8 FHP Euro screw lengths 18mm, 13mm, 7.5mm

Bottom panel thickness: 12.7 - 19mm (1/2" - 3/4") Back panel thickness: 16 - 19mm (5/8" - 3/4") Back panel height: min 146mm (5 3/4") Zargen 6136

117mm (4 5/8") Side Height




- Integrated drawer slide and drawer side
- Self-closing feature with 60mm (2 3/8") closing range
- Built-in drawer front bumpers
- Quick assembly through dowelled and integrated front fixing brackets
- White epoxy finish
- Tolerance adjustment 2mm (3/32")
- Load capacity: 100 lb
- Adjustments: Cam height (± 2mm), side (± 1.5mm)
- Made in the USA


Zargen 6136 slide, 100 lb (45 kg)



Description	Slide Length	Item No.	PU
Zargen 6136/350	350 (13 3/4")	22906-03	5
Zargen 6136/400	400 (15 3/4")	22907-03	5
Zargen 6136/440	440 (17 3/8")	22700-03	5
Zargen 6136/470	470 (18 1/2")	22701-03	5
Zargen 6136/510	510 (20 1/16")	22702-03	5
Zargen 6136/550	550 (21 5/8")	22703-03	5
Zargen 6136/400	400 (15 3/4")	22907-12	200
Zargen 6136/510	510 (20 1/16")	22702-12	200
Zargen 6136/550	550 (21 5/8")	22703-12	200




	Bottom Panel Length Extension		nsion	
Slide Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Single Stop	Double Stop
350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	280 (11")	-
400 (15 3/4")	381 (15")	378 (14 7/8")	300 (11 13/16")	314 (12 3/8")
440 (17 3/8")	421 (16 9/16")	418 (16 7/16")	340 (13 3/8")	354 (13 15/16")
470 (18 1/2")	451 (17 3/4")	448 (17 5/8")	370 (14 9/16")	384 (15 1/8")
510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	410 (16 1/8")	424 (16 11/16")
550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	450 (17 11/16")	464 (18 1/4")







Drawer Back and Bottom Measurements



Drawer Installation Measurements





*Allow minimum of 3mm (1/8") for bottom clearance. If screws are used, increase clearance accordingly.

Drawer slide attachment:

Wood screws #6 x 5/8 FHP Euro screw lengths 18mm, 13mm, 7.5mm

Bottom panel thickness: 12.7 - 19mm (1/2" - 3/4") Back panel thickness: 16 - 19mm (5/8" - 3/4") Back panel height: min 114mm (4 1/2")

1

Zargen 6036

85mm (3 3/8") Side Height




- Integrated drawer slide and drawer side
- Self-closing feature with 60mm (2 3/8") closing range
- Built-in drawer front bumpers
- Quick assembly through dowelled and integrated front fixing brackets
- White epoxy finish
- Tolerance adjustment 2mm (3/32")
- Load capacity: 100 lb
- Adjustments: Cam height (± 2mm), side (± 1.5mm)
- Made in the USA

Zargen 6036 slide, 100 lb (45 kg)




Description	Slide Length	Item No.	PU
Zargen 6036/270	270 (10 5/8")	11895-04	10
Zargen 6036/350	350 (13 3/4")	11896-04	10
Zargen 6036/400	400 (15 3/4")	12849-04	10
Zargen 6036/440	440 (17 3/8")	12850-04	10
Zargen 6036/470	470 (18 1/2")	12851-04	10
Zargen 6036/510	510 (20 1/16")	12852-04	10
Zargen 6036/550	550 (21 5/8")	11901-04	10
Zargen 6036/400	400 (15 3/4")	12849-16	400
Zargen 6036/440	440 (17 3/8")	12850-16	400
Zargen 6036/470	470 (18 1/2")	12851-16	400
Zargen 6036/510	510 (20 1/16")	12852-15	300
Zargen 6036/550	550 (21 5/8")	11901-15	300



Drawer Extension

	Bottom Panel Length Extension		nsion	
Slide Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Single Stop	Double Stop
350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	280 (11")	-
400 (15 3/4")	381 (15")	378 (14 7/8")	300 (11 13/16")	314 (12 3/8")
440 (17 3/8")	421 (16 9/16")	418 (16 7/16")	340 (13 3/8")	354 (13 15/16")
470 (18 1/2")	451 (173/4")	448 (17 5/8")	370 (14 9/16")	384 (15 1/8")
510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	410 (16 1/8")	424 (16 11/16")
550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	450 (17 11/16")	464 (18 1/4")













Drawer Back and Bottom Measurements with 6100 Railing Installation





Drawer Installation Measurements







*Allow minimum of 3mm (1/8") for bottom clearance. If screws are used, increase clearance accordingly.

Drawer slide attachment:

Wood screws #6 x 5/8 FHP Euro screw lengths 18mm, 13mm, 7.5mm

Bottom panel thickness: 12.7 - 19mm (1/2" - 3/4")Back panel thickness: 16 - 19mm (5/8" - 3/4")Back panel height: min 82 (3 1/4") Zargen 6026

85mm (3 3/8") Side Height




- Integrated drawer slide and drawer side
- Self-closing feature with 60mm (2 3/8") closing range
- Built-in drawer front bumpers
- Quick assembly through dowelled and integrated front fixing brackets
- White epoxy finish
- Tolerance adjustment 2mm (3/32")
- Load capacity: 100 lb
- Adjustments: height (± 2mm), side (± 1.5mm)
- Made in the USA

Zargen 6026 slide, 100 lb (45 kg)




Description	Slide Length	Item No.	PU
Zargen 6026/270	270 (10 5/8")	17766-04	10
Zargen 6026/350	350 (13 3/4")	17767-04	10
Zargen 6026/400	400 (15 3/4")	17768-04	10
Zargen 6026/440	440 (17 3/8")	11103-04	10
Zargen 6026/470	470 (18 1/2")	11128-04	10
Zargen 6026/510	510 (20 1/16")	17771-04	10
Zargen 6026/550	550 (21 5/8")	17772-04	10
Zargen 6026/400	400 (15 3/4")	17768-16	400
Zargen 6026/440	440 (17 3/8")	11103-16	400
Zargen 6026/470	470 (18 1/2")	11128-16	400
Zargen 6026/510	510 (20 1/16")	17771-16	400
Zargen 6026/550	550 (21 5/8")	17772-15	300



Drawer Extension

	Bottom Pa	Bottom Panel Length		nsion
Slide Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Single Stop	Double Stop
350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	280 (11")	-
400 (15 3/4")	381 (15")	378 (14 7/8")	300 (11 13/16")	314 (12 3/8")
440 (17 3/8")	421 (16 9/16")	418 (16 7/16")	340 (13 3/8")	354 (13 15/16")
470 (18 1/2")	451 (173/4")	448 (17 5/8")	370 (14 9/16")	384 (15 1/8")
510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	410 (16 1/8")	424 (16 11/16")
550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	450 (17 11/16")	464 (18 1/4")




Front Overlay + 9 (3/8")


PU - Packaging unit







Drawer Back and Bottom Measurements with 6100 Railing Installation





Drawer Installation Measurements







*Allow minimum of 3mm (1/8") for bottom clearance. If screws are used, increase clearance accordingly.

Drawer slide attachment:

Wood screws #6 x 5/8 FHP Euro screw lengths 18mm, 13mm, 7.5mm

Bottom panel thickness: 12.7 - 19mm (1/2" - 3/4")Back panel thickness: 16 - 19mm (5/8" - 3/4")Back panel height: min 82 (3 1/4") Zargen 6035

43mm (1 11/16") Side Height




- Integrated drawer slide and drawer side
- Self-closing feature with 60mm (2 3/8") closing range
- Built-in drawer front bumpers
- Quick assembly through dowelled and integrated front fixing brackets
- White epoxy finish
- Tolerance adjustment 2mm (3/32")
- Load capacity: 100 lb
- Adjustments: Cam height (± 2mm), side (± 1.5mm)
- Made in the USA


Zargen 6035 slide, 100 lb (45 kg)



Description	Slide Length	Item No.	PU
Zargen 6035/270	270 (10 5/8")	12119-04	10
Zargen 6035/350	350 (13 3/4")	12120-04	10
Zargen 6035/400	400 (15 3/4")	12121-04	10
Zargen 6035/440	440 (17 3/8")	12122-04	10
Zargen 6035/470	470 (18 1/2")	12123-04	10
Zargen 6035/510	510 (20 1/16")	12124-04	10
Zargen 6035/550	550 (21 5/8")	12125-04	10




	Bottom Pa	nel Length	Exter	nsion
Slide Length	16mm (5/8") Back Panel	19mm (3/4") Back Panel	Single Stop	Double Stop
350 (13 3/4")	331 (13 1/16")	328 (12 15/16")	280 (11")	-
400 (15 3/4")	381 (15")	378 (14 7/8")	300 (11 13/16")	314 (12 3/8")
440 (17 3/8")	421 (16 9/16")	418 (16 7/16")	340 (13 3/8")	354 (13 15/16")
470 (18 1/2")	451 (173/4")	448 (17 5/8")	370 (14 9/16")	384 (15 1/8")
510 (20 1/16")	491 (19 5/16")	488 (19 3/16")	410 (16 1/8")	424 (16 11/16")
550 (21 5/8")	531 (20 7/8")	528 (20 13/16")	450 (17 11/16")	464 (18 1/4")







Drawer Back and Bottom Measurements


Drawer Back and Bottom Measurements with 6100 Railing Installation





Drawer Installation Measurements





*Allow minimum of 3mm (1/8") for bottom clearance. If Screws are used, increase clearance accordingly.

Drawer slide attachment:

Wood screws #6 x 5/8 FHP Euro screw lengths 18mm, 13mm, 7.5mm


Bottom panel thickness: 12.7 - 19mm (1/2" - 3/4") Back panel thickness: 16 - 19mm (5/8" - 3/4") Back panel height: min 37.5mm (1 1/2")

TH

37.5

Zargen Soft-close

Damper set



- Add-on damper creates a smooth soft-close action for Zargen drawers
- Liquid closing mechanism for improved performance
- Three options for various load capacities
- Height adjustment ±2mm via elongated hole
- Secure striker plate engagement
- Actuator design allows for flush mounting
 - Set includes: damper and actuator unit

Soft-close Damper




Description	Load Capacity	Item No.	PU
15 kg Damper set	33 lb	02564-11	140
30 kg Damper set	66 lb	02572-11	140
70 kg Damper set	154 lb	02565-11	140

Note: Damper sets do not include screws.

Soft-close Damper Placement




Dampers per drawer




PU - Packaging unit






Mounting dimensions



Recommended screws are: #4 x 1/2" Phillips flat head wood screws #4 x 3/4" Phillips pan head wood screws




Zargen	А	В
43	16.5	43
85	58.5	85
117	90.5	117
149	122.5	149
213	186.5	213

6100 Railing System



- Designed for use with ZBox and Zargen Systems
- Easy to construct
- Allows end user to customize storage space
- Includes convenient rail dividers
- · Available in white

6100 Railing System



Front railing clip Dowelled






Back railing clip Dowelled



Back railing clip Screw-on




Divider railing clip



Back partition clip


Screw-on

Corner Bracket



Description	Slide Length	Item No.	PU
6100-02 Side Railing 345 (13 9/16")	350 (13 3/4")	F085098128211	20
6100-02 Side Railing 395 (15 9/16")	400 (15 3/4")	F085096773211	20
6100-02 Side Railing 435 (17 1/8")	440 (17 3/8")	F085096774211	20
6100-02 Side Railing 465 (18 5/16")	470 (18 1/2")	F085096775211	20
6100-02 Side Railing 505 (20")	510 (20 1/16")	F085096776211	20
6100-02 Side Railing 545 (21 3/8")	550 (21 5/8")	F085097210211	20
6100-02 Divider Railing - cut to size	Railing length 1000 (39 3/8")	F085096783211	20

Description	Item No.	PU
6150-01 Front railing clip, dowelled	F145096360111	20
6150-HF Front partition clip, 4.2mm screw-on	F145098829111	20
6150-02 Back railing clip, dowelled	F145096719123	100
6150-03 Back railing clip, 4.2mm screw-on	F145096769111	20
6150-20 Back partition clip, 4.2mm screw-on	F145097480111	20
6180-01 Divider railing clip	F145096770111	20
6190-01 Corner bracket, LH	F145096771111	20
6190-01 Corner bracket, RH	F145096772111	20



Pendaflex




6110 File Railing




- The Pendaflex Rail 6110 provides a lip for drop in file folders. It is cut to a desired length and attached over the 6100 side railing.
- Use in conjunction with ZBox and Zargen
- Easy to construct
- White plastic

File Rail 6110



Description	Length	Item No.	PU
Pendaflex Rail 6110	1100 (43 5/16")	F145099062211	20
Front railing clip, doweled, white		F145096360111	100
Back railing clip, doweled, white		F145096719123	100

Drawer Measurements




Inside Cabinet Width

ICW = Inside Cabinet Width Legal Size paper: ICW= 418mm (16 7/16") Letter size Paper: ICW = 342mm (13 7/16")


Drilling Patterns for Pendaflex File Drawers

Front panel


(manual and automatic assembly)







Back panel (manual assembly)



Pendaflex

File Railing




- Designed for use with metal drawer system or wood drawer application
- File bar accommodates lateral file application
- Easy to construct
- Available in white finish

US File Rail


Drawer Back

5

Note: Screw on bracket Slide in rail



Description	Use With Slide Length	Item No.	PU
US/468.5 Side Rail	470 (18 1/2")	01692-05	20
US/508.5 Side Rail	510 (20 1/16")	01690-05	20
US/548.5 Side Rail	550 (21 5/8")	01686-05	20
711 (28") File Bar		30890-05	20
Lateral File Clip		30954-39	20
US/442.5 Partition Rail	470 (18 1/2")	01693-05	20
US/482.5 Partition Rail	510 (20 1/16")	01691-05	20
US/522.5 Partition Rail	550 (21 5/8")	01687-05	20
Partition Bracket		30956-39	20



PU - Packaging unit

		Letter 303	(11 15/16")		
	I	Legal 379	(14 15/16")		1
	4				• •
2	000		37.5 (1 1/2")		000
2			37.3(11/2)		
				("2")	6")
				01/	6/1
				267 (10 1/2")	192 (79/16")
				2	-
1					
	0		37.5 (1 1/2")		1 -0


3595 Pendaflex Aluminum File Railing






- For Zargen and ZBox drawer systems
- Install file railing system independent from drawer system
- Front tilt adjustment
- Oval aluminum anodized

3595 File Rail




ZBox Installation Instructions



*6023 measurement used. For other drawer heights, refer to the appropriate page.


Zargen Installation Instructions



*6036 measurement used. For other drawer heights, refer to the appropriate page.

ZBox and Zargen

Pilaster Mounting Bracket



- Use 8mm Fits over 32mm line boring patterns hole with • Attaches to cabinet with Euro or
 - wood screwsAllows use of pilaster dowel on
 - cabinet member for an adjustable roll out shelf.Allows roll out shelves to be
 - adjustable in 32mm increments


Description	ltem No.	PU
Pilaster Mounting Bracket	30912-12	200

Pilaster Dowels



- Allows for construction of adjustable pull-outs with any Zargen Drawer Slide System when attached to cabinet member
- Dowel requires an 8mm x 5/8" deep hole
- Attaches with a #6 x 5/8" or #6 x 1/2" FHP screw

Pilaster Dowel, black	00395-43	500



Door/Drawer Protector



Attaches to side of wooden pull-out. Designed for inset pull-out trays for frame or frameless cabinetry.

Description	Item No.	PU
Door/drawer protector	13096-43	500

6036 Support Bracket



Attaches to the center of wide

- drawers for support.Elongated holes for drawer
- Elongated holes for drawer front adjustments.

Description	Item No.	PU
6036 Support bracket, nickel	22226-42	100

Central Locking Device



- Use with most commercial gang lock system.
 - Provides necessary match for gang lock pins to engage.
 - For 6023, 6036, and 6026

Description	Item No.	PU
Central locking device	F145088123238	300

PU - Packaging unit

ZBox and Zargen

6036 Spacer for Inset Drawers				
6.5mm (1/4")		Description	Item No.	PU
		6036 Spacer	00035-42	100
	CW - 44mm(1 3/4*)			
6195 Spacers for Cabinet Memb	ers Designed for doors protruding into the	Description	Item No.	PU
	achingt and for inpact draworg		F145 086 478 111	
		 6195 Spacer, 25mm 6195 Spacer, 11mm 	89104-39	20
		3 6195 Spacer/pin, 25mm	13097-39	20
•		S of yo opacery pin, 20mm	10077-07	20
Screws				
Screws		Description	Item No.	PU
Screws Euro Screw, Nickel-plated	ATTATA A	Description Euro Screw 11mm (7/16") Pozi	Item No. 499.360.61.1015	PU 500
Screws				
Screws		Euro Screw 11mm (7/16") Pozi	499.360.61.1015	500
Screws Euro Screw, Nickel-plated		Euro Screw 11mm (7/16") Pozi	499.360.61.1015	500
Screws Euro Screw, Nickel-plated		Euro Screw 11mm (7/16") Pozi Euro Screw 13mm (1/2") Pozi	499.360.61.1015 499.360.61.3015	500
Screws Euro Screw, Nickel-plated		Euro Screw 11mm (7/16") Pozi Euro Screw 13mm (1/2") Pozi Description	499.360.61.1015 499.360.61.3015	500 500
Screws Euro Screw, Nickel-plated		Euro Screw 11mm (7/16") Pozi Euro Screw 13mm (1/2") Pozi	499.360.61.1015 499.360.61.3015	500

G*

Zargen


Zargen Front Bracket



- Position bracket on the inside edge of the face frame with the tab resting on the cross rail.
- Brackets can be stapled or screwed.

Description	Item No.	PU
Zargen front bracket	00228-09	100

Roll-out Tray Bracket




•	Allows 6036/6026 slide to be
	used as roll out tray

- Tray front is 59mm (2 5/16")
- Bracket mounts to front of slide •
- Color: white

٠





12.7 (1/2")		-	
	0	59(2 5/16")	
		37.5	
ront panel = bottom panel width	-	(1 1 / 21)	

Po	lyb	ag	co	ns	si	sts	; C	of:	
-	-							-	

2 - Brackets, LH and RH 2 - Clamps

4 - #4 X 3/8", NI screws

Set consists of:


2 - Brackets, LH and RH

2 - Clamps

Roll-out Tray Bracket, Dowelled




- Allows 6036/6026 slide to be used as roll out tray
- Tray front is 76.2mm (3")
- For use with 5/8" (16mm) drawer front material
- Bracket mounts to the front of slide • • No need to remove the adjustment
- bracket · Color: white



6036/6026 Roll out tray bracket - Dowelled 30573-15 300

Set consists of:

2 - Brackets, LH and RH



PU - Packaging unit

ZBox & Zargen Mounting Brackets

Zargen


6196 Brac




- Attaches cabinet member of drawer slide if no side panel is available
- Bracket can be used for right or left
- Polybag includes 4 brackets
- with screws

Description	Item No.	PU
6196 Bracket	00432-08	50

- Polybag set consists of:
- 4 Brackets
- 8 Screws #10 x 5/8" PHP Screws





Rear Mounting Socket



- Drawer slide can slide in or out to achieve different cabinet depth
- Extra long length
- · Socket can be stapled or screwed

Description	Item No.	PU
Rear mounting socket, left	13946-09	100
Rear mounting socket, right	13947-09	100
Rear mounting socket, left	13946-17	500
Rear mounting socket, right	13947-17	500

ZBox

Inset Bracket Set



For ZBox face frame application, the inset bracket provides a simple solution to attach the cabinet member to the face frame without having to block out the cabinet.

- Bracket mounts behind the face frame, minimum 12.7mm (1/2")
- frame required Includes guide markings for proper setback of 37mm

Description	Item No.	PU
Inset bracket set	13901-37	1
Inset bracket set	13901-08	50

Polybag set consists of:

- 2 Universal Inset Bracket ABS Brown
- 2 8 X 32 Tapped Insert for Inset bracket
- 4 #7 X 2" mounting screws
- 2 #8 32 X 1/2" Machine Screw FHP
- 1 Instructions

	41 (1 5/8")	12.7 (1/2")
		0
73.6 (2 7/8")	<u> </u>	
13		10

Face Frame Brackets



Description	Item No.	PU
Face frame rear mount bracket	30200-09	100



Machinery

Grass PRO1 and ZRam for ZBox and Zargen Assembly

Grass PRO1 for ZBox and Zargen



• Depth stop can be adjusted to material thickness

- Functional design
- Easy, fast and efficient operation
- Easy maintenance
- 3 spindle gear box

Description	Item No.	PU
220v single phase pneumatic	80131	1
220v three phase pneumatic	80132	1
110v single phase pneumatic	80068	1




Description	Item No.	PU
Extension fence 300mm to 1250mm	88612-01	1


ZBox and Zargen Conversion Kit



Description	Item No.	PU
PRO1 Gear box	80151	1
2 PRO1 Side-to-side Stop	80153	1
3 PRO1 13mm Fence Stop	80152	1
4 PRO1 Kit (gear box, fence and side stops)	80154	1

Bits





Two 00222-01 bits are needed for the Zargen and ZBox Grass PRO1 setup.

This bit is designed for grooving and beveling the drawer bottoms for the lipped version of the ZBox and Zargen drawer slide. The bit comes only with a 1/2" shank.

De	escription	Item No.	PU
1 Ro	outer bit	00197-01	1
_			
De	escription	Item No.	PU
2 10	Omm Carbide counter sink drill bit, LH	00222-01	1

ZRam



• Designed for semi-automated assembly of ZBox and Zargen slides

- Operated by a foot pedal air required
- No adjustment required when using various heights or when switching slide types
- Economical solution for drawer assembly

ZRam 93250-01 1	Description	Item No.	PU
	ZRam	93250-01	1
ZRam Retrotit Kit 69401 1	ZRam Retrofit Kit	69401	1

PU - Packaging unit

ZBox and Zargen Assembly

Assembly of ZBox and Zargen

Grass PRO1

To assemble, drill drawer back dowel holes for each side by positioning back against the side-to-side stop.

To ensure correct positioning of the drawer front dowel holes, place drilled drawer back against right side of 13mm stop. Set floating side stop at opposite end of panel. Drill bits are countersunk to allow for easy installation of dowels.

To drill right side of drawer front, place front against the 13mm stop. To drill left side, place front against floating side stop.





ZRam

To insert the slide, position the slide against the ZRam arm and place drawer back over the dowel. Repeat for other side.

Place drawer front face down on ZRam. Position slide over dowel holes and depress foot pedal. Repeat for other side.

After assembly is complete, place drawer box on a stable surface and press bottom firmly over tabs.

Note: The same process is used for the assembly of both the ZBox and Zargen drawer systems.











GRASS America Inc. 1202 NC Highway 66 South Kernersville, NC 27284

Phone: 1-800-334-3512 Fax: 1-800-525-8406

www.grassusa.com info@grassusa.com GRASS Canada Inc. 10 Newgale Gate, Unit 7 Toronto, ON M1X 1C5

Phone: 1-800-461-4975 Fax: 1-416-335-5907

www.grasscanada.com info@grasscanada.com

