



## FINISH COMPARISON

	COMFORT DESIGNS COMPRESSION-MOLDED SOLID SURFACE	FORM BY COMFORT DESIGNS CAST SOLID SURFACE	CULTURED MARBLE	TILE AND GROUT	QUARTZ (ENGINEERED STONE)	LAMINATE
<b>Abrasive Cleaners</b>	Not affected	Can dull finish	Damages the gel coat	Can scratch the tile	Not affected	Damages product
<b>Heat &amp; Humidity</b>	Not affected	Expansion and contraction	Crazing and cracks	Not affected	Not affected	Expansion and contraction
<b>Color</b>	Runs all the way through	Runs all the way through	Surface only	Surface only	Runs all the way through	Surface only
<b>Installation</b>	Lightweight and easy to manage	Lightweight and easy to manage	Heavy and hard to manage	Long and difficult process	Heavy and specialized fabrication needed	Lightweight and easy to manage
<b>Durability</b>	Virtually indestructible	Somewhat brittle	Very brittle	Breakable - surface chips easily	Virtually indestructible	Breakable - surface can scratch easily
<b>Recycled Content Colors</b>	Yes	No	No	No	No	No
<b>Heat Resistance</b>	★★★★ Up to 450 degrees	★★★ Up to 365 degrees	★ Up to 120 degrees	★★★★ Exceeds 450 degrees	★★★ Up to 230 degrees	★ Up to 150 degrees
<b>Stain Resistant</b>	★★★★	★★★	★★	★★★★	★★★	★★★
<b>Impact Resistant</b>	★★★★	★★	★	★★★★	★★★★	★
<b>Scorch Resistant</b>	★★★★	★	★	★★★★	★★★	★
<b>Mold/Mildew Resistant</b>	★★★★	★★★★	★★★★	★	★★★★	★★★
<b>Chemical Resistant</b>	★★★★	★★	★★	★★★★	★★★★	★
<b>Renewable/Repairable</b>	★★★★	★★★	★	★	★	★
<b>Seamless Appearance</b>	★★★★	★★★★	★★★★	★	★★★★	★★
<b>Price</b>	\$\$	\$\$	\$	\$\$\$	\$\$\$\$	\$