

SLIDING SHOWER DOOR ESSENCE H

Features

- Double bypass sliding doors allow entry to the shower from the left and right sides
- Modern design gives the shower area an open and spacious feeling
- Specially designed rollers create a smooth, quiet gliding operation
- Anodized aluminum water guards accommodate out-of-plumb (uneven) walls up to a 1/4"
- Top guiderail can be trimmed up to 4" for width adjustment
- Towel bars on each glass panel double as handles
- Certified clear tempered glass is 5/16" (8mm) thick
- DreamLine exclusive ClearMax[™] protective coating is water-repellant and stain-resistant
- Hardware available in Chrome or Brushed Nickel finishes

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ANSI Z97. 1 (tempered glass)
- 16 CFR Part 1201

Specified Model

SHDR-6360760H-XX



Model	Description	Application	Glass Thickness	Frame Finishes/Colors
SHDR-6360760H-01	Sliding Shower Door	Shower	5/16"(8mm)	Chrome
SHDR-6360760H-04	Sliding Shower Door	Shower	5/16"(8mm)	Brushed Nickel

Product Specification

- 5/16" (8mm) thick clear tempered glass
- 56" (1422mm) to 60" (1524mm) finished wall opening
- 76" (1930mm) height
- 25 9/16" (650mm) Towel Bar
- 3 1/16" (78mm) min threshold requirement

INSTALLATION NOTES

Install this product according to the installation manual.

Please note that you should consult your local building codes with questions on installation compliance standards. Building and plumbing codes may vary by location, and DreamLine[®] is not responsible for code compliance standards for your project and will not accept any returns.

GENERAL NOTICE

- The installation surface needs to be leveled and rigid prior the assembly
- The wall structure needs to be plumbed and able to support total weight of the unit
- The installation process is required some adjustments, cutting and drilling.
- All primary surfaces need to be protected during installation
- The uneven surface level or out of square condition can result in serious problems with your installation.

A (Min-Max)	B (Height)	C (Walk-In)	D (Width)		
56"(1422mm) – 60"(1524mm)	76"(1930mm)	24"(610mm)-28"(711mm)	3 1/16"(77mm)		
SIDE ELEVATION FRONT ELEVATION					
PRODUCT DIAGRAM					

"The Essence H shower door (the "Product") is suitable for commercial installation and comes backed by the Dreamline's standard one (1) year commercial warranty under which Dreamline will repair or replace any defective Product during the warranty period. For commercial customers, we strongly recommend the use of Dreamline's Onsite Contractor Support option. Dreamline's commercial warranty does not apply to damage or losses resulting from (i) other than normal and proper use and normal service conditions; (ii) improper installation, (iii) installation in or upon an unsuitable surface or areas; (iv) abuse, (v) accident, (vi) alteration, (vii) misuse, (viii) neglect, (ix) unauthorized repair or the failure to utilize suitably qualified and trained persons to perform service and/or repair of the Product, (x) improper maintenance, (xi) failure to follow installation, operating, cleaning or maintenance instructions, and (xii) use of "non-authorized" parts. "

