Care & Cleaning CAST ACRYLIC | SOLID SURFACE | ACRYLX

To Clean the Unit

Simply use a household liquid detergentdiluted with warm water, or a vinegar and warm water solution with a soft sponge or cloth.

More persistent stains, tar, or paint can be removed with mineral spirits. Restore dull areas by rubbing with an automotive type body cleaning compound.

Cleaning Products to Consider

Test First Always test your cleaner on an inconspicuous area.

- Ivory® liquid dish soap
- Dawn® liquid dish soap
- Vinegar & Water Solution
- Mr. Clean® All-Purpose
- Lysol® Bathroom

Be sure to read the label and follow the cleaner's recommendations.





NO caustic or abrasive cleaners

NO harsh or gritty scouring powders

NO solvents, paint thinner or acetone solutions

NO wire brushes, metal scrapers or tools

Helpful Tip- Use Caution with Tools & Boots

Save the cardboard from the packaging and place it on the floor to stand on while working on the unit.

Whirlpool System Flush

The whirlpools system should be flushed periodically - not to exceed 90 days.

- Fill the tub with water 2 above the highest jet
- Add 1/2 oz. liquid dishwasher liquid per gallon of water
- Run the system for 10 minutes
- Drain the bath



Lysol® is a registered trademark of Reckitt Benckiser LLC and is not affiliated with the Praxis Companies.