

VP6036CTSM2

60 x 36 x 82



PROFESSIONAL

FEATURES

- Modern, matte finish
- Smooth, 4-piece kit
- Easy Wedge & Lock installation
- Caulkless installation
- Integral soap shelves
- Meets FHA Code Compliant Requirement 6 for Backing
- Available in White only
- 15 Year residential limited warranty

COMPONENTS OF KIT

Above Floor Rough (AFR)

- VP6036CTL (Tub) or VP6036CTR (Tub)
- VP6062CBW2 (Back Wall)
- VP2962CSW (Side Walls)

FHA Code Compliant

- VP6036CTL (Tub) or VP6036CTR (Tub)
- VP6062CBW2A (Back Wall)
- VP2962CSWA (Side Walls)

PACKAGED DIMENSIONS

- Tub: 63 x 40 ½ x 24 ½
- Back Wall: 65 x 61 ½ x 8 ½
- Side Wall Set: 64 ¼ x 32 ¼ x 5

VERITEK PRO

Lightweight and durable, Veritek™ Pro is produced with Swan Solid Surface, a proprietary SMC compound.

Veritek™ Pro is the better bathroom solution and is a snap to install!

Available in the Following Offerings:


Depth	Width	Height Standard	Height AFR	Model Number			
				Standard	FHA	AFR	FHA & AFR
36	60	79	82	VP6036CTS2L/R	VP6036CTS2AL/R	VP6036CTSM2L/R	VP6036CTSM2AL/R

- Standard: Base model shower, tub, or tub shower offering
- FHA Code Compliant Requirement 6 for Backing (FHA): Backing is included for future grab bar installation
- Above Floor Rough (AFR): Clearance for drain placement, eliminating the need for drain relocation
- FHA Code Compliant (FHA) & Above Floor Rough (AFR): A combination kit for FHA & AFR



VP6036CTSM2

60 x 36 x 82 inches



FEATURES Dimensional Tolerance $\pm 3/8"$. Dimensions needed for site preparation should be measured from the unit. Manufacturer assumes no responsibility for preparatory work.


Type	Model #	Material	Height	Drain	Net Wt. lbs	Pkg. Wt. lbs
AFR Tub-Shower	VP6036CTSM2L/R	Swan Solid Surface	82	LH or RH	158	173
FHA and AFR Tub-Shower	VP6036CTSM2AL/R	Swan Solid Surface	82	LH or RH	188	203

DIMENSIONS

Specifications	inches
Width: Overall / Net	60
Depth: Overall / Net	37 1/4 / 36
Height: Overall / Net	83 3/8 / 82
Enclosure Opening	56
Skirt Height	21
Drain Rough-In (from Back Wall)	17 3/8
Drain Rough-In (from Side Wall)	2
Drain: Diameter / Clearance	2 / 3 1/2

FRAMING DIMENSIONS

Type	D Depth	W Width	H Height	A	B	C
Alcove	37 1/4	60	83 3/8	Box Out	2	17 3/8




SUMP DATA

Top of Drain to Bottom of Overflow	Capacity to Overflow gal	WIDTH @ centerline		DEPTH @ centerline	
		Top	Bottom	Top	Bottom
12 5/8	52	50 1/2	42 5/8	27 3/8	22 3/8



VP6036CTSM2

 60 x 36 x 82
inches

 Backer Board

Applicable Standard Models

VP6030CTS2L/R
 VP6030CTSM2L/R
 VP6030CTSMIN2L/R
 VP6030CTSM2L/R
 VP6032CTSMIN2L/R
 VP6032CTSM2L/R
 VP6036CTS2L/R
 VP6036CTSM2L/R
 VP6042CTS2L/R
 VP6042CTSM2L/R

Applicable AFR Models

VP6030CTS2AL/R
 VP6030CTSM2AL/R
 VP6030CTSM2AL/R
 VP6030CTSMN2AL/R
 VP6032CTSM2AL/R
 VP6032CTSMN2AL/R
 VP6036CTS2AL/R
 VP6036CTSM2AL/R
 VP6042CTS2AL/R
 VP6042CTSM2AL/R