


## TOP VIEW



## SPECIFICATION SHEET


This shower enclosure shall be model XAB CUST SH Pan center drain. Finished surface shall be of a sanitary grade acrylic exhibiting a minimal thickness of 15 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have maximum outside dimensions of  $80" \times 60" \times 4"$ . The unit shall meet ANSI Z124.1-2, UPC, and CSA B45.5.

## HANDED BY THE DRAIN


The enclosure shall be equipped with the following features:

- I) Custom drain location,
- 2) Slip resistant pattern on floor,
- 3) Accessible shower threshold.



Custom Measurements						
	Min	Max	Customer			
А	TBD	80"				
В	TBD	60"				
С	8" from Right	8" from Left				
D	8" from Rear	8" from Front				
E	3"	TBD				

Please indicate necessary dimensions in 'Customer' column.



FINISHED WALLS ABOVE THE SHOWER BASE BY OTHERS.

Job Name	Approved By Print Name		Date	COMFORT DESIGNS	
Project No	Approved By Signature			Model No. XAB CUST SH Pan	
Comfort Designs 435 Industrial Road Savannah, TN 38372	Architect			Drawing No. XAB CUST SH Pan	
	Engineer			Date Issued. 1-10-24	Drawing Rev. 2-7-24
	Rep			Material. Cast Acrylic	
tel 800.443.7269	Wholesaler			Color.	
fax 731.925.4290 www.comfortdesignsbathware.com	Comments	Comments		Dimensions are in inches. Due to the nature of the materials dimensions may vary $\pm$ $_{1/2"}$	