

Heat-only thermostats with touchscreen

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Heat-only Thermostat with Touchscreen (A3100101) is a simple, non-programmable thermostat designed to sense room air temperature using operative temperature and/or floor temperature via an optional floor sensor (A9010599).



Part name	Part no.	A [inch]	B [inch]	C [inch]	Current draw max. [A]	Operating voltage AC [VAC]	Output rating at 24VAC [A]	Ambient humidity non-condensing max [%]	Weight per UOM [lbs/UOM]
Heat-only Thermostat with Touchscreen	A3100101	5.394	3.227	0.801	0.042	24	1.3	90	-
Slab Sensor, 10k	A9010599	-	-	-	-	-	-	-	-

Installation

Related applications

Install the thermostat on an interior wall of the desired zone approximately 5 feet above the floor. Do not mount the thermostat on a location that may be affected by localized heat sources or cold drafts. It may be necessary to install a draft barrier behind the thermostat to prevent air from blowing through the wiring hole which can affect the thermostat's built-in sensor. Refer to the Uponor Heat-only Thermostat with Touchscreen Installation and Operation Manual for more information.

Radiant heating systems

Notes

Floor sensor:
10K, J-curve thermistor

Ambient conditions:
10% to 90% humidity (non-condensing)

Sensor type: 10k J-curve

Tolerance: +/- 1% at 77°F (25°C)

Wire type: 22 gauge

IP68 continuous immersion 3m /10 ft

Footnotes

Contact information

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---