



Dual Voltage Cast Iron Shallow Well Jet Pump

- Durable cast iron pump body
- Built-in automatic thermal overload protection
- Dual voltage motor (115/230V), factory wired for 115V
- Pressure switch pre-set at 30-50 PSI
- 1-1/4" NPT suction and 1" NPT discharge
- For use on shallow well applications up to 25' water level
- Certified for sale in Canada by an accredited certification body
- Motor: 1/2 HP • Max. Flow Rate: 710 GPH
- Voltage: 230 V • Suction Head: 25'

Model No. DC662 Price/Each \$



Dual Voltage Cast Iron Convertible Jet Pump

- For use on shallow well applications up to 25' water level
- If deeper than 25', the pump can be easily converted to deep well operation (deep well pump, 25-80' water level)
- Durable cast iron pump body
- Built-in automatic thermal overload protection
- Dual voltage motor (115/230V), factory wired for 115V
- Ejector is included for deep well usage
- 1-1/4" NPT suction and 1" NPT discharge
- Certified for sale in Canada by an accredited certification body
- GPH at 40 psi discharge pressure:
0': 1460 GPH, 50': 1410 GPH, 100': 920 GPH, max. pressure shutoff 140'
- Motor: 1 HP • Max. Flow Rate 920 GPH
- Voltage: 230 V • Suction Head: 198'

Model No. DC664 Price/Each \$



Stainless Steel Housing-Cast Iron Base Sump Pump

- Certified for sale in Canada by an accredited certification body
- Stainless steel motor shell with durable cast iron volute
- Oil-filled permanent split capacitor motor
- Built-in automatic thermal overload protector
- Works with vertical or piggy back float switch for automatic operation
- Certified for sale in Canada by an accredited certification body
- 1-1/2" discharge
- 8' power cord



Model No.	HP	Volts	Amps	Max Flow Rate GPH	Price /Each
DC659	1/3	115	4.5	3630	
DC660	1/2	115	5	4400	

Submersible Utility Pump

- Certified for sale in Canada by an accredited certification body
- Corrosion-resistant, reinforced thermoplastic construction
- Bottom suction design filters debris and removes water down to 1/4" from surface
- Built-in automatic thermal overload protector motor
- 3/4" NPT discharge, 1 1/4" adapter included
- 10' power cord



Model No.	HP	Volts	Amps	Max Flow Rate GPH	Price /Each
DC651	1/3	115	4	2160	

Automatic Pool Cover Pump

- Automatically turns on when 2" of water is detected
- Corrosion-resistant, reinforced thermoplastic construction
- Bottom suction design filters debris and removes water down to 1/4"
- Certified for sale in Canada by an accredited certification body
- Built-in automatic thermal overload protector
- 25' power cord
- 3/4" NPT check valve adapter included
- Motor: 1/4 HP • Max. Flow Rate: 2310 GPH
- Voltage: 115 V • Suction Head: 20'

Model No. DC654 Price/Each \$



Plastic Column & Cast Iron Base Pump

- Certified for sale in Canada by an accredited certification body
- Polypropylene base • 8' power cord
- Corrosion-resistant vinyl column and drive shaft
- Fully adjustable automatic vertical float switch
- Top suction screened design prevents clogging
- 1-1/4" discharge • 1-1/2" adapter included
- Max. Flow Rate: 3270 GPH • Air Inlet: 1-1/4" NPT

Model No. DC657 Price/Each \$



Automatic Submersible Utility Pump

- Certified for sale in Canada by an accredited certification body
- Corrosion-resistant, reinforced hermoplastic construction
- Bottom suction design filters debris and removes water down to 1/4" from surface
- Permanent split capacitor motor and built-in automatic thermal overload protector
- 1" NPT discharge, 3/4" adapter included • 10' power cord
- Automatically turns on when 1-1/2" of water is detected; turns off when water level falls below 1/4"
- Motor: 1/3 HP • Max. Flow Rate: 2160 GPH
- Voltage: 115 V • Amps: 4 A

Model No. DC652 Price/Each \$



Portable Transfer Pump

- Built-in automatic thermal overload protection
- Convenient carrying handle for easy transport
- Certified for sale in Canada by an accredited certification body
- 3/4" NPT discharge
- 6' power cord
- Motor: 1/10 HP
- Max. Flow Rate: 264 GPH
- Voltage: 115 V • Suction Head: 46'

Model No. DC655 Price/Each \$



Cast Iron Sewage Pump

- Durable cast iron construction
- Built-in automatic thermal overload protector motor
- Adjustable tethered or piggy back float switch for automatic operation
- Certified for sale in Canada by an accredited certification body
- 2" NPT discharge • 10' power cord
- Motor: 1/2 HP • Max. Flow Rate: 3880 GPH
- Voltage: 115 V • Amps: 6.5 A
- Max. Diameter of Waste: 2"

Model No. DC661 Price/Each \$

