

Application:

General purpose gauge, for potable water pumps & systems, these gauges are suitable for compressors, hydraulic presses, machinery, pneumatic equipment and motors, for most commercial air, water and steam services. To be used with fluid medium which does not clog connection or corrode copper alloy. **Not for use with oxygen, natural gas or propane.**

NO LEAD TO CO.25% Pb by weighted avg.

Third Party Certified to NSF / ANSI 372

Certification:

NSF/ANSI Standard 372 Certified (No Lead Series Only)






GAUGE SPECIFICATIONS					
Standard	ASME B40.1				
Dial	4-1/2" (114mm) white aluminum dial				
Case	304 Stainless Steel				
Lens	Acrylic				
Ring (Bezel)	304 Stainless Steel				
Connection	Brass / No Lead Brass				
Bourdon Tube	Brass				
Fill Liquid	N/A				
Movement	Brass / No Lead Brass				
Pointer	Aluminum (Anodized Black)				
Welding	Tin Solder				
Working Pressure	Maximum 75% of Full Scale Value (F.S.V.)				
Ambient Op. Temp.	-40°F to 140°F (-40°C to 60°C)				
Media Op. Temp.	Max. 140°F (60°C)				
Accuracy	+/- 1% Full Scale Value				
Enclosure Rating	General Purpose				
15 - 600 PSI	Tapped but restrictor screw not included				




25 Whaley Avenue, PO Box 310, Milverton, ON CANADA NOK 1M0 Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164

www.boshart.com







DIMENSIONS						
Part No.	No Lead Part No.	Connection	Range	Increments	Weight	
			PSI		grams	
N/A	PG45-15NL	1/4" MPT	0-15	0.2	300	
N/A	PG45-30NL	1/4" MPT	0-30	0.5	300	
N/A	PG45-60NL	1/4" MPT	0-60	1	300	
N/A	PG45-100NL	1/4" MPT	0-100	1	300	
N/A	PG45-160NL	1/4" MPT	0-160	2	300	
N/A	PG45-200NL	1/4" MPT	0-200	2	300	
N/A	PG45-300NL	1/4" MPT	0-300	5	300	
N/A	PG45-400NL	1/4" MPT	0-400	5	300	
N/A	PG45-600NL	1/4" MPT	0-600	10	300	
VACUUM GAUGE				'	,	
PGV45-30	N/A	1/4" MPT	30-0Hg	0.5	300	
COMBINATION V	ACUUM / PRESSURE GAU	GE				
PGC45-30-30	N/A	1/4" MPT	30Hg-0-30	0.5	300	



25 Whaley Avenue, PO Box 310, Milverton, ON CANADA NOK 1M0 Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164

www.boshart.com