

APPLIANCE CONNECTOR - STATIONARY (ACS)

Applications:

Gas appliance Connectors for Household Kitchens, Utility Rooms, Laundry Rooms, Pulse Combustion Furnaces (AGAL), Forced Air Heating Units, Rooftop HVAC Units, Campfire Log Sets, and Fireplaces.

STAINLESS STEEL GAS CONNECTORS (Stationary) FOR DOMESTIC APPLIANCES

- ANSI Z21.24 - C.S.A. 6.10 "Indoor/Outdoor"
- ANSI Z1.75-6.27 "Manufactured Homes"



Nominal Connector Series (ID, Inches)	ACS Series Gas Appliance Connector BTU Capacity / Hr. - NATURAL GAS (Flow capacities are based 0.64 specific gravity @ 0.5" w.c. pressure drop)							
	12"	18"	24"	30"	36"	48"	60"	72"
1/4	48,000	43,800	40,000	36,400	33,400	28,300	24,900	23,100
3/8	102,000	93,100	85,000	77,100	71,100	60,500	53,200	49,100
1/2	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000
3/4			290,900	270,500	255,900	215,000	197,400	173,900
1			581,800	545,200	515,900	442,700	398,900	347,800

Nominal Connector Series (ID, Inches)	ACS Series Gas Appliance Connector BTU Capacity / Hr. - PROPANE (Flow capacities are based 1.53 specific gravity @ 0.5" w.c. pressure drop)							
	12"	18"	24"	30"	36"	48"	60"	72"
1/4	75,000	68,438	62,500	56,875	52,188	44,219	38,906	36,094
3/8	159,375	145,469	132,813	120,469	111,094	94,531	83,125	76,719
1/2	281,250	256,563	234,375	212,500	195,313	165,625	145,625	134,375
3/4			454,531	422,656	399,844	335,938	308,438	271,719
1			909,063	851,875	806,094	691,719	623,281	543,438

50, 250, 375 Series
AVAILABLE WITHOUT
COATING



250 & 375 Series
AVAILABLE WITH BLACK
COATING - WHISTLE FREE



The above stationary connectors may be used with: Natural, manufactured, mixed liquefied petroleum gases, and LP gas-air mixtures. The added protection of stainless steel is especially useful in areas where the natural gas has a high sulfur content.

TO BE INSTALLED BY LICENSED GAS FITTERS ONLY.