

WiderSlider™

Adjustable Galvanized Bracket



User Friendly

Pilot holes allow for faster 2-eared DE-90 installations. When a 3-eared DE-90 is preferred, secure the fitting with self-tapping screws.

Each bracket has pre-dimension hash marks for more precise installations and the tabs are easily bendable offering 3/4", 1-1/2" or 2-1/8" depths within the stud cavity.

Pre-assembled

Pre-assembled and fully adjustable with interlocking tab to secure safe overlap and prevent disassembly. Available in two lengths for 16" and 24" stud bays.

Durable & Reliable

WiderSlider™ adjustable brackets are 1-3/8" wide x 22-gauge high quality G90 pre-galvanized steel. Best of all, they're made in the USA.



Supply Drainage Support

www.siouxchief.com

TAKE THE FIELD.



Installation Guidelines



1. Bend tabs to accommodate 3/4", 1-1/2" or 2-1/8" depths from face of stud.

2. Secure bracket to stud or floor joist with at least 4 screws (not included).

3. Secure DE-90 elbow, pipe clamps, or tube straps directly to bracket.

Pilot holes allow for faster 2-eared DE-90 installations. When a 3-eared DE-90 is preferred, secure the fitting with any self-tapping screw.



Completely adjustable to fit a range of depths to align with the shower valve.



520-616



Ideal for 24" metal stud bays.



520-626

» Buying Information

ITEM NO.	DESCRIPTION	PKG	MIN QTY	CASE QTY
WIDERSLIDER™				
520-616	For 16" stud bays with 9" - 15" adjustability	B	50	50
520-626	For 24" stud bays with 13" - 23" adjustability	B	50	50

PACKAGING:
B = Bulk



24110 South Peculiar Drive
Peculiar, Missouri 64078
P 1.800.821.3944
F 1.800.758.5950

DISTRIBUTED BY



Made in the USA

