

CLEAR VINYL TUBE (JFT TUBE)

Applications: It is clear, flexible, easy to clean, abrasion resistant and non-contaminating.

It is suitable for the conveyance of air, and water and is used extensively where food and beverages are conveyed.

Certain Sizes Now Available
Packaged x 10 Ft. (Series JFTA)



CERTIFIED UNDER STANDARD 51 and 61

Clear polyvinyl-chloride tube is manufactured from F.D.A. approved resins.

It is clear, flexible, easy to clean, abrasion resistant and non-contaminating.

It is suitable for the conveyance of air, and water and is used extensively where food and beverages are conveyed.

NOTE

THE WORKING PRESSURES LISTED FOR THE VINYL TUBE IS RATED AT +70°F, +21°C. ANY AMBIENT OR INTERNAL INCREASE IN TEMPERATURE WILL LOWER THE ABOVE LISTED WORKING PRESSURES. THIS TUBE IS NOT RECOMMENDED FOR MILK CONTACT, ALCOHOL (LIQUOR) OR MEDICAL APPLICATIONS.

PART No.	O.D.	I.D.	FT.
JFTA-42-10P	1/4	1/8	10
JFTA-53-10P	5/16	3/16	10
JFTA-64-10P	3/8	1/4	10
JFTA-75-10P	7/16	5/16	10
JFTA-86-10P	1/2	3/8	10

- **PACKAGING:** 100 FT COILS 1/8" TO 1-1/4" I.D.
500 FT REELS 1/8" TO 1/2" I.D.
300 FT REELS 5/8" TO 1" I.D.
50 FT COIL 1-1/2" I.D.

NOTE: TO ORDER REEL LENGTHS CHANGE -100 TO -REEL

- **TEMPERATURE:** +25°F TO +149°F, -4°C TO +65°C
- **FITTINGS:** HOSE BARBS
- * **THESE ITEMS ARE ALSO AVAILABLE IN REELS.**
(CHANGE -100 TO -REEL)

PART No.	Tube O.D. (IN.)	Actual I.D. (IN.)	Working Pressure (P.S.I.)
JFT-42-100	1/4	1/8	65
JFT-53-100	5/16	3/16	55
JFT-63-100 *	3/8	3/16	65
JFT-64-100	3/8	1/4	55
JFT-74-100 *	7/16	1/4	60
JFT-75-100 *	7/16	5/16	50
JFT-84-100 *	1/2	1/4	70
JFT-85-100	1/2	5/16	60
JFT-86-100	1/2	3/8	45
JFT-106-100 *	5/8	3/8	55
JFT-108-100	5/8	1/2	30
JFT-128-100	3/4	1/2	45
JFT-1210-100*	3/4	5/8	30
JFT-1310-100*	13/16	5/8	30
JFT-1410-100	7/8	5/8	40
JFT-1612-100	1	3/4	35
JFT-1812-100	1-1/8	3/4	50
JFT-2014-100 *	1-1/4	7/8	35
JFT-2016-100	1-1/4	1	25
JFT-2416-100 *	1-1/2	1	35
JFT-2420-100 *	1-1/2	1-1/4	20
JFT-3224-50	2	1-1/2	35