

**90-380**

90-360 thru 90-486 Relays

Heavy-duty general purpose relay operates in any position.

Features

- Compact, totally enclosed design
- For heating and cooling applications and general switching
- Quiet, reliable and economical



Specifications

Temperature range.....-40°F to 150°F
 Mechanical life (no load) 1,000,000 operations, 120 operations/min.
 Electrical life (rated load) 100,000 operations, 6 operations/min.
 Load test making inrush rating (0.4 to 0.5 P.F.)
 Breaking 100% continuous rating (0.65 to 0.8 P.F.)
 Coils, frequency.....50 / 60 Hz
 Coils, insulation..... Class B
 Coils, termination 1/4" Quick Connect
 Coils, operate 85% of nominal coil voltage; 110% maximum safe operate
 Coils, duty cycle.....Continuous
 Weight.....2.3 oz.
 UR/CUR file number..... E12139
 CSA/CUS certificate number LR13360

90-360 thru 90-486 Relays

Coil voltage ac (50/60 hz)	Switch action	Res dc ohms	Coil data nom. Current ma	Coil data nominal va sealed	Inrush va	Model number	Item number
24	SPNO	77	125	3	4	90-360	90 360S1
24	SPDT	77	125	3	4	90-370	90 370S1
24	SPNO/SPNC	77	125	3	4	90-380	90 380S1
120	SPNO	2,000	25	3	4	90-362	90 362S1
120	SPDT	2,000	25	3	4	90-372	90 372S1
208/240	SPDT	6,050	12.5	3	4	90-374	90 374S1
208/240	SPNO/SPNC	6,050	12.5	3	4	90-384	90 384S1
277	SPNO	10,300	10.8	3	4	90-466	90 466S1
277	SPDT	10300	10.8	3	4	90-476	90 476S1
277	SPNO/SPNC	10300	10.8	3	4	90-486	90 486S1

Wiring diagrams

**SPNO / SPNC****SPDT****SPNO**

90-360 THRU 90-486 RELAYS Contact Rating

Inductive	Resistive
12 Amps. Continuous, 60 Amps. Inrush @ 125 VAC	18 Amps. Continuous @ 277 VAC
8 Amps. Continuous, 48 Amps. Inrush @ 250 VAC	

