

C-CON™ CONVERTER BOX

Allows Most Control Panels to Utilize the C-Level™ CL40 Floatless Sensor

The C-Con™ converts the signal from a C-Level™ CL40 sensor to simulate float levels (up to four floats). Activation levels can be conveniently set and adjusted at the C-Con™ box by using the output dials, eliminating the need to go into the tank to move float tether points. Works well in wastewater pump tanks, confined space applications, and systems with high grease content.

Note: The C-Con™ converter box can be used with most panels using control switches for pump down applications. The C-Con™ converter box is not recommended for use with plugger type panels or intrinsically safe type panels.

FEATURES

- NEMA 1 rated for indoor use; can be mounted in a control panel
- Green power on indicator
- Four independently adjustable output set points at the converter box with red LED status indicators
- Adjustable pump start/stop and alarm levels from converter box
- Simulate button for testing proper wiring of outputs
- Factory-installed output and power wires
- Works with most simplex or duplex control panels
- Alternative to mercury float switches
- Utilizes the innovative floatless C-Level™ Sensor
- Five-year limited warranty on C-Con™ Converter Box
- Two-year limited warranty on C-Level™ Sensor

OPTIONS

This system is available with:

- C-Level™ CL40 Sensor with 25' Vented Cable
- C-Level™ CL40 Sensor with 50' Vented Cable
- C-Level™ CL40 Sensor with 100' Vented Cable
- C-Level™ CL40 Sensor with 200' Vented Cable
- C-Level™ CL40 Sensor with 300' Vented Cable
- Without C-Level™ CL40 sensor



C-Level™ Sensor US Patent No.
8,567,242; 8,336,385 and 8,650,949.



Level Monitoring
Controls



C-CON™ CONVERTER BOX (120V) - Converts any float-operated control panel to utilize the C-Level™ CL40 floatless sensor.

Part #	Description	Shipping Weight	List Price
1093696	C-Con™ Converter Box w/C-Level™ CL40 Sensor with 25' Vented Cable	2.44 lbs.	\$791.00
1093699	C-Con™ Converter Box w/C-Level™ CL40 Sensor with 50' Vented Cable	3.13 lbs.	\$838.00
1093702	C-Con™ Converter Box w/C-Level™ CL40 Sensor with 100' Vented Cable	4.51 lbs.	\$933.00
1093705	C-Con™ Converter Box w/C-Level™ CL40 Sensor with 200' Vented Cable	7.27 lbs.	\$1,123.00
1093727	C-Con™ Converter Box w/C-Level™ CL40 Sensor with 300' Vented Cable	10.03 lbs.	\$1,313.00
1031067	C-Con™ Converter Box without C-Level™ CL40 sensor	1.08 lbs.	\$390.00

SPECIFICATIONS

VOLTAGE: 120 VAC, 60Hz, 44mA

OUTPUT CONTACT RATING: 3 amp, 240 VAC

ENCLOSURE: 3 x 4.25 x 1.25 inches (7.62 x 10.79 x 3.81 cm), NEMA 1 thermoplastic