



NAPCO, a Westlake company
 131 Regalcrest Court, Woodbridge, ON L4L 8P3
 Tel: 905.856.7550 ■ Fax: 905.856.4367

TECHNICAL SPECIFICATION

NAPCO PVC Rigid Conduit Fittings Strain Relief Connectors RSRC15, RTSRC10, RTSRC15

SCOPE

This specification covers the requirements for PVC (polyvinyl chloride) Rigid Conduit Strain Relief Connectors, both threaded and non-threaded. Nominal sizes of ¾"-non-threaded (RSRC15) and ½", ¾"-threaded (RTSRC10, RTSRC15) are available.

MATERIALS

The strain relief connectors and grommets are manufactured from flexible (grommets) and rigid (connector and threaded nut) virgin PVC compound. The threaded strain relief connectors are sold complete with a rubber O-Ring and locknut.

GROMMETS

6 Flexible PVC grommets are supplied with each strain relief connector. The grommets are sized to accommodate the following cord sizes:

Grommet Style	Cord Range	
	From	To
	Width = 0.195"	Width = 0.285"
	Length = 0.450"	Length = 0.530"
	Width = 0.220"	Width = 0.291"
	Length = 0.516"	Length = 0.565"
	Diameter = 0.525"	Diameter = 0.625"
	Diameter = 0.240"	Diameter = 0.300"
	Diameter = 0.290"	Diameter = 0.385"
	Diameter = 0.405"	Diameter = 0.500"



TEST REQUIREMENTS

Quality testing is as per NAPCO's Quality Control program