

## VINYL ELECTRICAL TAPE



**HIGHLY CONFORMABLE**

**CSA/UL APPROVED**

### DESCRIPTION

Special vinyl film backing coated with a non-corrosive adhesive. Excellent conformability. CSA approved with a temperature range of -7°C to 80°C. Colours: 02 Red, 05 Yellow, 07 Green, 08 Blue, 10 White.

### MAIN FEATURES

- PVC has excellent memory.
- Very conformable.
- Temperature range.
- Water resistant.
- CSA/UL approved for -7°C to 80°C (19°F to 175°F).

### APPLICATIONS

- Splicing of appliances wires.
- Repairs in junction boxes.
- Insulation of wires.
- Used as a masking tape in electro plating.
- All electrical splicing.
- Wrapping battery cables.
- Protection against solvents and corrosion.

### TECHNICAL DATA

Colour .....	Black(01), Red(02), Yellow(05), Green(07)
.....	Blue(08), White(10)
Backing .....	PVC film
Adhesive .....	Natural rubber
Thickness .....	7 mil
Dielectric Strength .....	7000 volts
Adhesion .....	18 lb/in
Tensile Strength .....	20 lb/in
Elongation .....	225%
Temperature Resistance .....	-7°C to 80°C (-19.4°F to 176°F)
Meets CSA Spec .....	LR 31971
Meets UL Spec.....	E - 50292

**Please note:**

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.