TECHNICAL BROCHURE

BCELEACC R4

ELECTRICAL ACCESSORIES

• REPLACEMENT MOTOR LEADS • CABLE ACCESSORIES

• LIGHTNING PROTECTION DEVICES • BULK CABLE • PACKAGED CABLE



FEATURES

Motor Leads:

• 4" and 6" CentriPro Motor Leads

Cable Accessories:

• Heat Shrink Kits

Bulk cable with ground:

- Twisted design, solid copper conductor
- PVC insulated
- AWG 8-14

Packaged Cable for 4" CentriPro Motors

- No splice required, connector threads into motor.
- 2 and 3 wire with ground
- Lengths from 50' to 300'
- Twisted design stranded wire

4" CENTRIPRO MOTOR LEADS

Order No.	Description
AW348C	3 wire 48" with ground and (2) screws
AW3100C	3 wire 100" with ground and (2) screws
AW248C	2 wire 48" with ground and (2) screws
AW2100C	2 wire 100" with ground and (2) screws

6" CENTRIPRO MOTOR LEADS

Order No.	Description	Used On
CPML-12	150", 12 / 4	5-15 HP 1Ø; 5 - 25 and 40 HP, 3Ø
CPML-10	150", 10 / 4	30 and 50 HP, 3Ø
CPML-8	150", 8 / 4	Optional for 30-50 HP, 3Ø

Packaged Cable for 4" Submersible Motors

FOR CENTRIPRO 4" MOTORS

Length in Feet	3-wire Order No.	2-wire Order No.
50	ACPC3050	ACPC2050
100	ACPC3100	ACPC2100
150	ACPC3150	ACPC2150
200	ACPC3200	ACPC2200
250	ACPC3250	ACPC2250
300	ACPC3300	ACPC2300

• AWG 12, stranded copper, twisted design with ground.

• XLPE - suitable for potable water.

• No underwater splice required.

• CentriPro motor connector attached.



Xylem Inc. 2881 East Bayard Street Ext., Suite A Seneca Falls, NY 13148 Phone: (866) 325-4210 • Fax: (888) 322-5877 www.centripro.com CentriPro is a trademark of Xylem Inc. or one of its subsidiaries.

CentriPro is a trademark of Xylem Inc. or one of its subsidiaries © 2016 Xylem Inc. BCELEACC R4 November 2016

Bulk Cable with Ground

AWP15

- Reel lengths 500' or 1000', 2 or 3 wire with ground
- UL listed, NEC standard
- PVC insulated, 600 V, 60°C
- Twisted design
- Solid copper conductor sizes: 14, 12, 10, 8

BULK CABLE

В

PVC insulation with ground

Order No.	Size No.	Length
AWP15-145	14 3-wire	500 ft.
AWP15-141	14 3-Wile	1000 ft.
AWP152-145	14 2-wire	500 ft.
AWP152-141	14 Z-WITE	1000 ft.
AWP15-125	12 3-wire	500 ft.
AWP15-121	12 S-WITE	1000 ft.
AWP152-125	12 2-wire	500 ft.
AWP152-121	12 Z-WITE	1000 ft.
AWP15-105	10.3-wire	500 ft.
AWP15-101	10 S-wire	1000 ft.
AWP152-105	10.2-wire	500 ft.
AWP152-101	IUZ-WIre	1000 ft.
AWP15-85	8 3-wire	500 ft.
AWP15-81	0.5-wire	1000 ft.

Sold only in reels.

HEAT SHRINK TYPE WIRE SPLICE KITS



Order No.	Shrink Tubes	Butt Connectors	Use on
AW25-3	4	(4) # 8	#8 - #12 Wire
AW25-4	4	(4) # 10 - #12	#10 - #14 Wire
AW25-5	3	(3) #10 - #12	#10 - #14 Wire
AW25-6	3 Large & 3 Small	None	#6 - #14

Use for making waterproof connections on submersible cable. Mandatory for use on underwater splices where variable speed drives are used.