


C2G
A brand of **legrand**

HDMI[®] CORE SOLUTIONS



COMMERCIAL A/V CONNECTIVITY

HDMI® is the most popular audio/video connection in commercial environments. Carrying both uncompressed audio and video at resolutions up to 4K, HDMI serves as a versatile platform for designing commercial audio video systems. The C2G HDMI product portfolio includes solutions that are a must have in all installations from the board room to the classroom.



HDMI ADAPTER RINGS

The Patent Pending HDMI Adapter Rings from C2G are the perfect addition to conference rooms, huddle spaces, lecture halls or classrooms to make sure that anyone can connect. Available in three different configurations, the C2G HDMI Adapter Rings provide ultimate flexibility to fit the needs of any space.

Item #	Mounting Location	Standard Adapters			Maximum Resolution	Maximum Refresh Rate	Retractor Maximum Extension	Optional Adapters	
		USB-C to HDMI	DisplayPort to HDMI	Mini DisplayPort to HDMI				VGA + Stereo Audio to HDM	Apple Lightning to HDMI
29878	HDMI Cable				4K	60Hz*	—	✓	✓
29879	Flat Surface (table or lectern)	✓	✓	✓			4.9ft		
29880	Table Box								

*USB-C to HDMI Adapter only. DisplayPort & Mini DisplayPort to HDMI Adapters support 4K 30Hz maximum

C2G PERFORMANCE SERIES HDMI CABLES

C2G Performance Series HDMI cables are designed, manufactured, and tested to deliver ultimate performance. These cables provide features that make them an ideal solution for commercial AV installations in Corporate, Government, Healthcare, Higher Education and K-12 School applications.



Compact Overmold



Integrated Finger Grips



Gripping Connector Shell

C2G PERFORMANCE SERIES FEATURES INCLUDE:

100% Testing

100% of cables are tested at the production line to ensure that it meets our standards—providing the peace of mind that it will perform as expected in the field.

Rated Cable Jackets

Each cable jacket is rated to the highest standard required for the installation location—reducing the time and complexity required to select the right cable.

Commercial Grade Connectors

The connectors feature a compact overmolding with integrated finger grips on all sides making these cables easy to insert and remove in limited access spaces and high-density environments. Additionally, the gripping connector shell provides two times the port retention of a standard connector reducing the chances of an accidental disconnect.

Lifetime Warranty

All C2G Performance Series Cables are backed by a lifetime warranty providing the peace of mind that C2G stands behind these products.

C2G PERFORMANCE SERIES ULTRA-FLEXIBLE HDMI CABLES

The C2G Performance Series Ultra Flexible HDMI Cables are the ideal solution for in-rack, in-wall, or short connections on a conference room table or lectern. The CMG/FT4-rated jacket meets the highest standard required for in-wall installation and the ¼ inch (6.5mm) minimum bend radius makes these cables perfect for installations in any tight space or high-density environment.



Item #	Length (ft)	Signal Type	Connector	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter (in)	Minimum Bend Radius (in)	Jacket Rating
C2G10373	1	HDMI 2.0	Gripping	18Gbps	4K	60Hz	0.2in	0.25in	In-wall CMG (FT4)
C2G10374	18in								
C2G10375	2								
C2G10376	3								
C2G10377	6								
C2G10378	10								

PREMIUM CERTIFIED HDMI CABLES


Premium High Speed HDMI Cables support all HDMI 2.0 features and have been tested to conform with the Premium HDMI Cable Certification Program for highest performance and ultra-reliability.



Item #	Length (ft)	Signal Type	Connector	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter (in)	Minimum Bend Radius (in)	Jacket Rating
50181	3	HDMI 2.0	Gripping	18Gps	4K	60Hz	0.25	2.5	In Wall, CMG
50182	6								
50184	10								
50185	12								
50186	15						0.37	3.7	
50188	20								

AV OVER IP FOR DIGITAL SIGNAGE

The AV over IP solution from C2G stream HDMI audio/video signals at up to a 4K resolution over a network or the Internet, making it an ideal solution for digital signage installations across multiple verticals.



AV OVER IP FEATURES:

- Supports an input resolution of up to 4K at 30Hz and an output resolution of up to 4K at 60Hz
- Video wall and multi-view capable, increasing the flexibility to meet the needs of any application
- Utilizes low-bandwidth H.264/H.265 video codec making it ideal for LAN & Internet transmissions
- Scalable matrix switching applications support over 600 sources and displays
- Serial RS232 and directional IR control signal provide complete control of distributed A/V systems
- Conveniently powered through PoE by a PoE(PSE) Ethernet switch
- Easy setup and system management through the Network Controller for HDMI over IP web interface or smartphone app

Retail & Restaurants



Corporate



Security



Education





AV OVER IP

This AV over IP solution streams HDMI audio/video at up to a 4K resolution over a network or the Internet. Multiple configurations offer the flexibility to support a digital signage system, video wall, and point to point extension, including multi-view capabilities.

Item #	Function/Type	Signals Streamed	Streaming Codec	Maximum Extension Length (ft)	Maximum Resolution	Maximum Refresh Rate	Special Features
29975	Encoder Box	HDMI Serial RS232 Infrared (IR)	H.264/ 265	328**	4K	30Hz	—
29976	Decoder Box					60Hz	Upscales HDMI output resolution to 4K 60Hz



NETWORK CONTROLLER FOR AV OVER IP

Item #	Description	Function
29977	Network Controller	Enables remote configuration of an AV over IP system including video wall and digital signage management. Accessed via web interface or smartphone app.



AV OVER IP ACCESSORIES

These accessories pair with the AVover IP to create a complete system.

Item #	Description	Function
29979	16-Port Rack Mount	Enables up to 16 AV over IP devices to be mounted within 3RU of rack space
29984	Blank Filler Plate for 16-Port Rack Mount	Fills empty spaces within the rack mount bracket to enable airflow management
29985	Replacement Mounting Bracket for 16-Port Rack Mount	Replace missing or damaged device mounting brackets included with the 16-Port Rack Mount
29983	Wall Mount Bracket	Enables an AV over IP device to be mounted to a wall or other flat surface



HDBaseT EXTENDERS

These HDBaseT Extenders are the perfect solution for point-to-point AV extensions with options for 4K HDMI, VGA along with USB data, Serial, and IR control. Each of these kits, along with the individual receivers, have a single HDMI output for the display.



HDBaseT KITS

Item #	Audio/Video Input(s)				Data & Control			HDBaseT Chipset	Max Bandwidth	Max Ext. Length (ft)	Max Res.	Max Frame Rate	TX Type & Color	RX Type & Color	Powered Side
	HDMI	USB-C A/V	VGA	Stereo Audio	USB	Serial RS232	Infrared (IR)								
C2G30010	✓	—	—	—	—	—	—	VS010	10.2Gbps	130ft*	4K	60Hz	Black Box	Black Box	TX or RX
C2G30011	✓	✓	—	✓	✓	—	—	VS210					Dual Gang Decorative Wall Plate White	Black Box	RX
C2G30012	✓	—	✓	✓	✓	—	—	VS210					Dual Gang Decorative Wall Plate White	Black Box	RX



HDBaseT TRANSMITTERS AND RECEIVERS

Item #	Audio/Video Input(s)/Output(s)				Data & Control			HDBaseT Chipset	Max Bandwidth	Max Ext. Length (ft)	Max Res.	Max Frame Rate	Function	TX Type & Color	Compatible TX/RX	Powered Side
	HDMI	USB-C A/V	VGA	Stereo Audio	USB	Serial RS232	Infrared (IR)									
C2G30019	✓ (2)	✓	—	✓	✓	—	—	VS210	10.2Gbps	130ft*	4K	60Hz	TX	Dual Gang Decorative Wall Plate White	C2G30020	RX
C2G30020	✓	—	—	—	✓	✓	✓	VS210					RX	Black Box	C2G30019	RX



HDBaseT CERTIFIED CATEGORY 6A PATCH CABLES

These cables are certified by the HDBaseT organization and are designed for use with HDBaseT Extenders.

Item #	Length (ft)	Color	Wiring Scheme	Conductor Size	Shielding	Cable Diameter (in)	Minimum Bend Radius (in)	Jacket Rating
43171	35	Blue	568B	23AWG	Discontinuous	0.27	2.65	Plenum, CMP
43172	50							
43173	75							
43174	100							
43175	150							
43176	200							
43177	250							
43178	300							



CAT6a CABLES

These Cat6a cables pair with HDBaseT or AV over IP solutions to create a complete AV extension system. Additional lengths available at C2G.com

	Grey	Blue	Black	Aqua	Green	Red	Yellow	Orange	Purple	White	Pink
20ft	00668	00702	00736	00770	50792	50811	50754	50849	50830	50773	50868
25ft	00669	00703	00737	00771	50793	50812	50755	50850	50831	50774	50869
30ft	00670	00704	00738	00772	50794	50813	50756	50851	50832	50775	50870
35ft	00671	00705	00739	00773	50795	50814	50757	50852	50833	50776	50871
50ft	50885	50877	50881	50873	50796	50815	50578	50853	50834	50777	50872
75ft	50886	50878	50882	50874	—	—	—	—	—	—	—
100ft	50887	50879	50883	50875	—	—	—	—	—	—	—
150ft	50888	50880	50884	50876	—	—	—	—	—	—	—



CAT6 CABLES

These Cat6 cables pair with HDBaseT or AV over IP solutions to create a complete AV extension system. Additional lengths available at C2G.com.

	Grey	Blue	Black	Green	Red	Yellow	Orange	Purple	White	Pink
20ft	03971	03979	03987	03996	04005	04014	04023	04032	04041	04056
25ft	27135	27145	27155	27175	27185	27195	27815	27805	27165	04057
30ft	03972	03980	03988	03997	04006	04015	04024	04033	04042	04058
35ft	31350	31351	31352	31354	31355	31356	31358	31357	31353	04059
50ft	27136	27146	27156	27176	27186	27196	27816	27806	27166	04060
75ft	31360	31361	31362	31364	31365	31366	31368	31367	31363	04061
100ft	27137	27147	27157	27177	27187	27197	27817	27807	27167	04062
125ft	27138	27148	27158	27178	27188	27198	27818	27808	27168	—
150ft	27139	27149	27159	27179	27189	27199	27819	27809	27169	04063

HDMI CONFERENCING SOLUTIONS

Increase the agility of your conferencing spaces with these innovative solutions from C2G.



29878
UNIVERSAL 4K HDMI
ADAPTER RING

29879
RETRACTABLE UNIVERSAL MOUNT
4K HDMI ADAPTER RING

29880
RETRACTABLE TABLE BOX MOUNT
4K HDMI ADAPTER RING

HDMI ADAPTER RINGS



MOUNTING OPTIONS

Three different mounting options provide the flexibility for you to choose what best meets the needs of your room.

- Universal Cable Mount attaches directly to an HDMI cable (5-10mm diameter)
- Retractable Universal Mount attaches to any flat surface, like a table or lectern
- Retractable Table Box Mount attaches to a Wiremold® AVIP®, Extron® MAAP™, and FSR® IPS™ opening in a table box



ESSENTIAL A/V ADAPTERS

Don't worry about having the right connections anymore. Standard configurations include the adapters to connect nearly any device to the in-room display.

- USB-C® to HDMI
- DisplayPort™ to HDMI
- Mini DisplayPort to HDMI

Add even more connectivity with these optional adapters:

- VGA and Audio to HDMI
- Apple® Lightning® to HDMI



COLOR CODING

Each adapter is color coded with a band that saves time and frustration by making it easy to quickly identify the adapter you need, "I need the yellow one".



PULL TAB


Easily grab the adapters when you need them with the integrated Pull Tab. Also, the pull tab may be customized to feature your company or organization logo*.

*Minimum order quantities apply



4K RESOLUTION

Maximize the performance of the in-room display and provide the detailed images required for analytical or detailed decision making. All adapters in the standard configurations support up to a 4K video resolution.



TOOLS INCLUDED

No more overnight orders or digging to find the right installation tools—everything you need to attach the adapters is included.

The HDMI Cable Gauge Tool eliminates the guess work and reduces the time you need to mount the Universal Cable Mount to the HDMI cable.

CONFERENCE ROOM VIDEO HUB



29974
CONFERENCE ROOM VIDEO HUB



ENABLES SCREEN SHARING

Switch between up to two HDMI and two USB-C devices to the display over a single HDMI Cable.



4K RESOLUTION

Maximized the performance of the in-room display at a 4K 60Hz resolution, helping to enable improved comprehension and detailed decision making.



BEAUTIFUL DESIGN

The design makes the hub look like it belongs on any tabletop. This means that you won't have to cut a hole to install.



SIMPLIFIED OPERATION

Switching between devices is made easy:

- Manually switch between devices using the top button
- Auto switch to a device by connecting and return to the previous device on disconnect

Integrated CEC control automatically switches the display to the correct input for the hub.

True plug-and-play with no software, app, or driver required. Simply connect, share, and switch.



SECURITY IN MIND

Secure the hub utilizing either the available Kensington® Security Slot or the optional mounting plate that utilizes the integrated PEM® fasteners on the bottom of the hub for mounting on or underneath the tabletop.



CONNECTIVITY INCLUDED

- 3ft HDMI and 3ft USB-C cable
- Power Supply





HDMI ADAPTER CABLES

These HDMI Adapter Cables allow a direct connection between a source device and display that do not share the same ports.

Item #	Length (ft)	Source Connector	Display Connector	Bi-directional	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter (in)	Minimum Bend Radius (in)	Jacket Rating
42513	1.6 (0.5m)	HDMI	DVI-D	✓	10.2Gbps	1080p	60Hz	0.22	2.2	PVC
42514	3.3 (1m)									
42515	4.9 (1.5m)									
42516	6.6 (2m)									
42517	9.8 (3m)									
42518	16.4 (5m)									
40286	1.6 (0.5m)	HDMI	DVI-D	✓	10.2Gbps	1080p	60Hz	0.29	2.9	In Wall, CL2
40287	3.3 (1m)									
40288	6.6 (2m)									
40289	9.8 (3m)									
40291	23 (7m)									
40292	32.8 (10m)									
50617	1.5	HDMI	HDMI Mini	✓	18Gbps	4K	60Hz	0.24	2.8	PVC
50618	3									
50619	6									
50620	10									
50614	3	HDMI	HDMI Micro	✓	18Gbps	4K	60Hz	0.17	2.8	PVC
50615	6									
50616	10									
26906	1	USB-C	HDMI	—	18Gbps	4K	60Hz	0.17	1.8	PVC
26888	3									
26889	6									
26896	10				10.2Gbps	4K	30Hz	0.29	2.9	
26890	15									
50193	3	DisplayPort	HDMI	—	18Gbps	4K	60Hz	0.24	2.4	PVC
50194	6									
50195	10									
54324	15						0.26	2.4		
54325	3	DisplayPort	HDMI	—	10.2Gbps	1080p	60Hz	0.26	2.4	PVC
54326	6									
54327	10									
54432	3	DisplayPort	HDMI	—	10.2Gbps	4K	30Hz	0.29	2.9	PVC
54433	6									
54434	10									
54420	3	Mini DisplayPort	HDMI	—	10.2Gbps	1080p	60Hz	0.26	1.2	PVC
54421	6									
54422	10									
54435	3	Mini DisplayPort	HDMI	—	10.2Gbps	4K	30Hz	0.19	1.9	PVC
54436	6									
54437	10									



HDMI SIGNAL CONVERTERS AND COUPLERS

These HDMI Signal Converters and Couplers are the perfect solution for extending the functional life of a device, display, or cabling infrastructure.

Item #		Source Connector	Display Connector(s)	Bi-directional	Style	Cable Length (in)	Maximum Resolution	Maximum Refresh Rate	Special Features
Black	White								
30548	—	HDMI (M)	HDMI (F)	✓	Adapter	—	1080p	60Hz	360° Rotating
40420	—	HDMI (M)	HDMI (F)	✓	Adapter	—	1080p	60Hz	180° Flexibility
40999	—	HDMI (M)	HDMI (F)	✓	Adapter	—	1080p	60Hz	90° Down Exit
43290	—	HDMI (M)	HDMI (F)	✓	Adapter	—	4K	60Hz	90° Right Exit
43291	—	HDMI (M)	HDMI (F)	✓	Adapter	—	4K	60Hz	90° Left Exit
18400	—	HDMI (F)	HDMI (F)	✓	Adapter	—	4K	60Hz	90°
40970	—	HDMI (F)	HDMI (F)	✓	Adapter	—	4K	60Hz	—
18408	—	HDMI (M)	HDMI Mini (F)	✓	Adapter	—	1080p	60Hz	—
18406	—	HDMI (M)	HDMI Micro (F)	✓	Adapter	—	1080p	60Hz	—
22323	—	HDMI (M), USB-A (M)	DisplayPort (F)	—	Dongle	7.5	4K	30Hz	—
54179	—	HDMI (F)	DisplayPort (F)	—	Box	—	1920x1200	60Hz	—
18401	—	HDMI (M)	DVI-D (M)	✓	Adapter	—	1080p	60Hz	—
40745	—	HDMI (M)	DVI-D (F)	✓	Adapter	—	1080p	60Hz	—
41352	—	HDMI (M)	DVI-D (F)	✓	Dongle	6	1920x1200	60Hz	—
41350	—	HDMI (M)	VGA (F)	—	Dongle	6	1080p	60Hz	—
41351	—	HDMI (M)	VGA (F), 3.5mm (F)	—	Dongle	6	1080p	60Hz	—
40714	—	HDMI (F)	VGA (F), 3.5mm (F)	—	Box	—	1920x1200	60Hz	—
40434	—	HDMI Mini (M)	HDMI (F)	✓	Adapter	—	1080p	60Hz	180° Flexibility
40435	—	HDMI Mini (M)	HDMI (F)	✓	Adapter	—	1080p	60Hz	—
41353	—	HDMI Mini (M)	VGA (F)	—	Dongle	6	1080p	60Hz	—
41354	—	HDMI Mini (M)	VGA (F), 3.5mm (F)	—	Dongle	6	1080p	60Hz	—
41355	—	HDMI Mini (M)	DVI-D (F)	✓	Dongle	6	1920x1200	60Hz	—
41356	—	HDMI Mini (M)	HDMI (F)	✓	Dongle	6.5	1920x1200	60Hz	—
18407	—	HDMI Micro (M)	HDMI (F)	✓	Adapter	—	1080p	60Hz	—
41357	—	HDMI Micro (M)	HDMI (F)	✓	Dongle	5	1080p	60Hz	—
41358	—	HDMI Micro (M)	DVI-D (F)	✓	Dongle	5	1920x1200	60Hz	—
41359	—	HDMI Micro (M)	VGA (F), 3.5mm (F)	—	Dongle	5	1080p	60Hz	—
18402	—	DVI-D (F)	HDMI (F)	✓	Adapter	—	1080p	60Hz	—
40746	—	DVI-D (M)	HDMI (F)	✓	Adapter	—	1080p	60Hz	—
26884	26885	USB-C (M)	HDMI (F), VGA (F)	—	Dongle	6	HDMI - 4K VGA - 1080p	HDMI - 30Hz VGA - 60Hz	USB-C Power Delivery
30547	—	USB-A (M)	HDMI (F)	—	Dongle	40	1080p	60Hz	—
54306	—	DisplayPort (M)	HDMI (F)	—	Dongle	6	4K	30Hz	Active Adapter
54151	—	DisplayPort (M)	HDMI (F)	—	Adapter	—	1080p	60Hz	—
54322	—	DisplayPort (M)	HDMI (F)	—	Dongle	8	1080p	60Hz	—
54293	—	DisplayPort (M)	HDMI (F) x 2	—	Dongle	11.8	4K	30Hz	Dual Display (MST)
54431	—	DisplayPort (M)	HDMI (F)	—	Dongle	8	4K	30Hz	—
28273	28274	DisplayPort (M)	HDMI (F), VGA (F)	—	Dongle	8	HDMI - 4K VGA - 1920x1200	HDMI - 30Hz VGA - 60Hz	—
54340	—	DisplayPort (M)	HDMI (F), VGA (F), DVI (F)	—	Dongle	9.8	HDMI - 4K DVI - 1920x1080 VGA - 1920x1080	HDMI - 30Hz DVI - 60Hz VGA - 60 Hz	—
54307	54308	Mini DisplayPort (M)	HDMI (F)	—	Dongle	6	4K	30Hz	Active Adapter
54313	54314	Mini DisplayPort (M)	HDMI (F)	—	Dongle	8	1080p	60Hz	—
54430	—	Mini DisplayPort (M)	HDMI (F)	—	Dongle	8	4K	30Hz	—
54292	—	Mini DisplayPort (M)	HDMI (F) x 2	—	Dongle	8	4K	30Hz	Dual Display (MST)
28271	28272	Mini DisplayPort (M)	HDMI (F), VGA (F)	—	Dongle	8	HDMI - 4K VGA - 1920x1200	HDMI - 30Hz VGA - 60Hz	—
54341	—	Mini DisplayPort (M)	HDMI (F), VGA (F), DVI (F)	—	Dongle	9.8	HDMI - 4K DVI - 1920x1080 VGA - 1920x1080	HDMI - 30Hz DVI - 60Hz VGA - 60 Hz	—
41410	—	VGA (F), 3.5mm (F)	HDMI (F)	—	Box	—	1080p	60Hz	—



HDMI DEVICES

These HDMI devices provide solutions for splitting an HDMI signal to multiple displays, switch between devices connected to a single HDMI port, or in-line extension over HDMI cabling.

Item #	Input Ports	Output Ports	Maximum Resolution	Maximum Refresh Rate	Special Features
29974	HDMI (2), USB-C (2)	HDMI	4K	60Hz	Auto Switch, CEC Control
40349	HDMI (2)	HDMI	1080p	60Hz	Auto Switch
40734	HDMI (3)	HDMI	1080p	60Hz	Auto Switch
41396	HDMI (3)	HDMI	4K	60Hz	—
41397	HDMI (5)	HDMI	4K	60Hz	—
40814	HDMI, VGA, 3.5mm	HDMI	1080p	60Hz	—
40850	HDMI, USB-C, Mini DisplayPort, VGA, 3.5mm	HDMI	HDMI - 4K USB-C - 4K Mini DisplayPort - 4K VGA - 1080p	HDMI - 60Hz USB-C - 60Hz Mini DisplayPort - 60Hz VGA - 60Hz	—
41389	HDMI (4)	HDMI (2)	4K	30Hz	Matrix Switch
41057	HDMI	HDMI (2)	4K	30Hz	—
41058	HDMI	HDMI (4)	4K	30Hz	—
42394	HDMI	HDMI	4K	60Hz	82ft extension @ 4K 164ft extension @ 1080p
40848	HDMI, DisplayPort, VGA, 3.5mm	HDMI	HDMI - 4K DisplayPort - 4K VGA - 1080p	HDMI - 30Hz DisplayPort - 30Hz VGA - 60Hz	—



HDMI CABLE LOCK

Item #	Description	Function
40744	HDMI Cable Lock	Add locking capability to any HDMI cable to prevent accidental cable disconnects.



HDMI VOLTAGE INSERTERS

The HDMI Voltage Inserters help to avoid hot plug, EDID and HDCP errors caused when proper voltages are not present in a HDMI system.

Item #	Input Connector	Output Connector	Power Connector	Maximum Resolution	Maximum Refresh Rate	Power Cable Length (in)	Voltage Delivered	Amperage Delivered
42223	HDMI (M)	HDMI (F)	NEMA 1-15P	4K	60Hz	72	5V	1A
42236	HDMI (M)	HDMI (F)	USB-A	4K	60Hz	70	5V	500mA



WALL PLATES

These wall plates provide a clean, professional looking transition to in-wall or in-furniture cabling.

Item #	Size/Style	Available Ports						Cutouts		Color
		HDMI	USB	VGA	Stereo Audio [3.5mm]	Composite Video [RCA]	Stereo Audio [RCA]	Keystone	Decorative	
03345	Keystone Insert	✓	—	—	—	—	—	—	—	White
39710	Decorative	✓	—	—	—	—	—	—	—	White
41042	Decorative	✓	—	—	—	—	—	—	—	Aluminum
41043	Decorative	✓	—	—	—	—	—	—	—	White
41045	Decorative	✓	—	—	—	—	—	—	—	Black
39875	Decorative	✓ - 2	—	—	—	—	—	—	—	Aluminum
39711	Decorative	✓	—	—	—	—	—	✓	—	White
39872	Decorative	✓	—	—	✓	—	—	—	—	White
39702	Decorative	✓	✓	—	—	—	—	—	—	White
39873	Decorative	✓	✓	—	✓	—	—	—	—	White
41031	Decorative	✓	—	✓	✓	—	—	—	—	White
39878	Single Gang	✓	—	—	—	—	—	—	—	Black
39870	Single Gang	✓	—	—	—	—	—	—	—	Aluminum
39879	Single Gang	✓ - 2	—	—	—	—	—	—	—	Black
60160	Single Gang	✓	—	—	—	—	—	✓ - 2	—	Aluminum
60161	Single Gang	✓	—	—	—	—	—	✓ - 2	—	White
39874	Single Gang	✓	✓	—	—	—	—	—	—	Aluminum
39871	Single Gang	✓	—	—	✓	—	—	—	—	Aluminum
39706	Single Gang	✓	✓	✓	✓	—	—	—	—	White
39707	Single Gang	✓	✓	✓	✓	—	—	—	—	Aluminum
41034	Single Gang	✓	—	✓	✓	—	—	—	—	Aluminum
60144	Single Gang	✓	—	✓	✓	—	—	—	—	Aluminum
39705	Single Gang	✓	—	✓	✓	—	—	✓	—	Aluminum
39708	Double Gang	✓ - 2	—	—	—	—	—	—	✓	White
39703	Double Gang	✓	✓	✓	✓	—	—	—	—	Aluminum
39704	Double Gang	✓	—	✓	✓	✓	✓	—	—	Aluminum
39877	Double Gang	✓	—	✓	✓	—	—	—	✓	White



HDMI CABLES

These HDMI Cables are the perfect solution for desktop connections, like connecting a laptop to a monitor, or connecting a laptop or tablet to a AV system in a classroom or conference room.

Item #	Length (ft)	Signal Type	Connector	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter (in)	Minimum Bend Radius (in)	Jacket Rating
56781	1	HDMI 2.0	Standard	18Gbps	4K	60Hz	0.24	2.4	PVC
50606	1.5								
50607	2								
56782	3								
50608	4								
50609	5								
56783	6								
50610	8								
56784	10								
50611	12								
50612	15								



FLEXIBLE HDMI CABLES

These Flexible HDMI Cables feature a flexible cable construction with a low profile, compact connector design making them an ideal fit for installations in tight spaces.

Item #	Length (ft)	Signal Type	Connector	Maximum Bandwidth	Maximum Resolution	Maximum Refresh Rate	Cable Diameter (in)	Minimum Bend Radius (in)	Jacket Rating
41361	1	HDMI 2.0	Low Profile	18Gbps	4K	60Hz	0.14	0.25	PVC
41362	2								
41363	3								
41364	6								
C2G41398	10	HDMI 1.4		10.2Gbps	1080p				



HDMI MINI & MICRO CABLES

These HDMI Mini and Micro cables are designed to connect mobile devices, like cameras and tablets, to a standard HDMI display.

Item #	Length (ft)	Signal Type	Connector	Maximum Bandwidth	Maximum Resolution	Maximum Frame Rate	Cable Diameter (in)	Minimum Bend Radius (in)	Jacket Rating
50617	1.5	HDMI 2.0	Mini HDMI	18Gbps	4K	60Hz	0.24	1.65	PVC
50618	3								
50619	6								
50620	10	HDMI 1.4	10.2Gbps	1080p					
50613	1.5	HDMI 2.0	Micro HDMI	18Gbps	4K		0.17	1.16	
50614	3								
50615	6								
50616	10					HDMI1.4			10.2Gbps



WIRELESS HDMI

A simple way to make a wireless, in-room AV connection from an HDMI device to display.

Item #	Maximum Extension	Maximum Resolution	Maximum Refresh Rate	Wireless Signal	Frequency Range	Displays Supported
29329	100ft	1080p	60Hz	Wireless Display (WiDi)	2.4/5Ghz	1
29512						2



C2G®

www.c2g.com

USA P 800.CABL.911 E trg@c2g.com

A brand of  **legrand®**

©2021 Legrand AV Inc. 200381 Rev B 01/21 C2G, Chief, Da-Lite, Luxul, Middle Atlantic, and Vaddio are registered trademarks of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio