



baresque.com.au e [info@baresque.com.au](mailto:info@baresque.com.au)  
p 1300 306 399

**baresque**

# **SERAPHIC DIGITAL PRINT**

## installation guide

**PLEASE CAREFULLY INSPECT YOUR CUSTOM DIGITAL PRINT PRODUCT PRIOR TO INSTALLING, CUTTING, OR FABRICATING AND INFORM BARESQUE (1300 306 399) IMMEDIATELY OF ANY DAMAGE OR DEFECTS. FAILURE TO DO SO MAY JEOPARDIZE YOUR RIGHTS TO WARRANTY REPLACEMENT AND / OR REIMBURSEMENT FOR SHIPPING DAMAGE.**

The following information is provided to assist you in the installation of our main seraphic digital print offerings. This information should be used as a guide only and Baresque recommend using accredited installers where possible. Baresque's recommended installers can be found [here](#) or at [baresque.com.au/faq/](http://baresque.com.au/faq/).

## **Handling**

Baresque Seraphic Digital Print wallcovering will arrive as palletised sheets. When handling sheet material, make sure hands are clean and oil free: cotton gloves are recommended especially for custom finishes and lighter colours.



[baresque.com.au](http://baresque.com.au) e [info@baresque.com.au](mailto:info@baresque.com.au)

# SERAPHIC DIGITAL PRINT

## Zintra installation guide (cont.)

### Overview

Please inspect carefully upon receipt of Baresque Zintra Acoustic Panel, replacement policy does not allow for any labour charges incurred during or after fabrication on the defective materials. The following list is a mandatory check list for fabricators when working with Baresque Zintra Acoustic Panel:

- Please check piece sizes, colour, design, finishing prior to fabrication or install
- Surfaces need to be flattened prior to install.
- Clean surfaces with denatured alcohol before applying adhesive to prevent bonding failure.

Baresque Panels are simple to install using construction adhesive and if desired double sided tape. It can be fixed directly to a timber frame wall or it can be laid over an existing wall lining, such as plaster board.

### IMPORTANT NOTES

- Do not rush. Take time & care during installation to achieve a professional finish.
- DO NOT USE SOLVENT BASED CONTACT ADHESIVES

Baresque panels can also be installed with different systems, such as:

NEUTRAL CURE SILICONE

SPLIT BATTEN

DOUBLE SIDED TAPE

PIN FIXING OR CABLE SYSTEM (Please contact Baresque to supply)

For more detailed information regarding fabrication and handling please reference Zintra Acoustic Panel install guide. Every application requires special attention and if unsure of which fixing method to use please contact Baresque custom service.

### Cleaning:

Blot excess spills from material quickly as possible. Wipe with a damp cloth. If stains persist, apply small amounts of carpet shampoo cleaner mixed with water and a damp cloth. Blot well after each application. Try this cleaning method in an inconspicuous place prior to a visible area.