



<b>10 Colorways:</b>	CH21-01 Lapis	CH21-08 Carved*
	CH21-02 Alabaster	CH21-09 Aragonite
	CH21-03 Sculpted	CH21-10 Limestone
	CH21-06 Agate*	CH21-11 Terracotta
	CH21-07 Soapstone	CH21-13 Verdigris
*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.		
<b>Total Weight</b>	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	<b>Vertical Repeat</b> 18 in.
<b>Roll Width</b>	52-54 in. (132-137 cm.)	<b>Horizontal Repeat</b> 52 in.
<b>Backing</b>	Non-Woven	<b>Nominal Pattern Width</b> 51 in.
<b>Tensile (Minimum)</b>	50 x 55 lbf (222 x 245 N)	<b>Match Information</b> Non-Reverse Hang, Straight Match
<b>Tear (Minimum)</b>	25 x 25 lbf (111 x 111 N)	<b>WA Spec.</b> WA-101, Type II
<b>Federal Spec.</b>	CCC-W-408D, Type II	<b>ASTM F-793</b> Category V, Type II
<b>Fire Testing</b>	NFPA 101® Life Safety Code®	
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup>	
	<ul style="list-style-type: none"> <li>- Class A Rating</li> <li>- Flame Spread - 10</li> <li>- Smoke Developed - 5</li> </ul>	
	NFPA 286 Corner Burn Test <sup>2</sup>	
	- Meets requirements for Flame Spread, Smoke Developed, & Flashover	
	1 When applied to GRC board with A-848-B adhesive    2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive	
<b>CE Certification</b>	EU classification in accordance with EN 15102:2007 + A1:2011	
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices	

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association  
 ©2022 Koroseal Interior Products, LLC.