

PEBBLED PRODUCT SPECIFICATIONS

Application
Upholstery

Content
100% Polyurethane, Breathable

Backing
65% Polyester, 35% Rayon

Width
54"

Repeat
N/A

General Characteristics

- Abrasion: 200,000+ double rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 15+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Tearing Strength (ASTM D2262)
- Adhesion of Coating (ASTM D751)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2

Cleaning


W/S, Bleach (4:1)

Environmental

- PVC/Phthalate Free
- No added FR/Anti-Bacterial
- Complies with Healthier Hospitals

Country of Origin

South Korea



Mineral



Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks