



### Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% PVC Vinyl
Backing	75% Polyester, 25% Cotton
Weight	36.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Taiwan
Collection	Vinyl Binder

### Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant

### Performance Characteristics

Abrasion Resistance ASTM D4157	50,000 Double Rubs
Break Strength ASTM D751-06	Warp: 67 lbs / Weft: 83 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 5.6 lbs / Weft: 6.2 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 68 lbs / Weft: 65 lbs
Wet Crocking AATCC 8	Grade: 4
Dry Crocking AATCC 8	Grade: 4.5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 9.6 lbs / Weft: 9.9 lbs
Cold Crack -20 Degrees	

### Flammability

- FMVSS 302
- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260