

SEBAGO PRODUCT SPECIFICATIONS

Application
Upholstery

Content
100% Polyurethane

Backing
100% Polyester

Finish
Graffiti-Free®

Width
54"

Repeat
N/A

General Characteristics

- Abrasion: 500,000+ Double Rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 15+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Tearing Strength (ASTM D2262)
- Adhesion of Coating (ASTM D751)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2

Cleaning

W/S, Bleach (4:1)

Environmental

- DMF-Free
- PVC/Phthalate Free
- No added FR/Anti-Bacterial
- Complies with Healthier Hospitals & CAL 01350

Country of Origin

South Korea




Caspian



Cloud Mist Md. Chocolate Mustard Seed Pecan Cordovan




Tawny Mocha Burmese Moonless Chestnut




Earth Dk. Fudge D. Black

glazed



Persimmon Meadow Reef Brique Mink



Merlot Bordeaux Ultra Marine Espresso S. Black

Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 Double Rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks