

N A P O L I P R O D U C T S P E C I F I C A T I O N S

Application

Upholstery

Content

Face-100% Silicone, Inherently Graffiti-Free®
Middle-100% Polyurethane (CPU)

Backing

100% Polyester

Width

54"

Repeat

N/A

General Characteristics

- Abrasion: Exceeds 500,000 double rubs (Wyzenbeek)
- Hydrolysis: 15+ weeks (ISO 1419)
- Tearing Strength (ASTM D2262)
- Adhesion of Coating (ASTM D751)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2;

Cleaning

W/S, Bleach (10:1)

Environmental

- DMF Free,
- PVC/Phthalate Free
- No added FR/Anti-Bacterial
- Complies with Healthier Hospitals & CAL 01350

Country of Origin

China



Mushroom



Glacial



Enoki



Mineral




Moat




Rhine




Squash




Ridge



Ruby




Marlin



Clay



Crow



Harbor

Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 Double Rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks