### **Nubbly**

66265 Arctic

# **Stinson**<sup>®</sup>

### **Nubbly**

Wild Kingdom Collection

#### **Performance Summary**

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- · Bleach-solution cleanable

#### **Environmental**

- · GREENGUARD Gold Certified
- LBC Red List Free
- · REACH Compliant
- Recycled content
- Non PFOA Stain Resistance
- · No added flame retardants
- No added antimicrobials

#### **Cleaning and Maintenance**

Cleaning Code: **(W-S)** For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

Bleach solutions of up to 10% may be used for more difficult stains.

Dye lots may vary slightly.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Specifications	<b>#</b> ♥**★A
Content	81% UV Polyester, 14% Post Consumer Recycled Polyester, 2% Polyester, 2% Post Industrial Recycled Polyester, 1% Nylon
Finish	Non-PFOA / Non-PFAS / Water-Based Stain Resistant
Backing	Acrylic
Weight	28.16 oz./lin. yd. ± 1 oz.
Width	54 inches
Roll Size	55 yards
	Made in the USA
Performance Characteristics	
Abrasion Resistance ASTM D-4157	Exceeds 75,000 double rubs - heavy duty
Break Strength ASTM D-5034	Warp: 313 lbs. min., Fill: 271 lbs. min.
Tear Strength ASTM D-2261	Warp: 104 lbs. min., Fill: 112 lbs. min.
Seam Slippage ASTM D-4034	Warp: 42 lbs. min., Fill: 63 lbs. min.
Brush Pilling ASTM D-3511	Class 3.0 min.
Colorfastness to Light AATCC-16	40 Hours, Class 4.0
Crocking AATCC-8	Dry: Class 4.0, Wet: Class 3.0
Flammability*	
California Technical Bulletin 117-2013 Section 1	Passed
NFPA 260	Class 1
UFAC	Class 1



# Stinson

C.F. Stinson, LLC 2849 Product Drive Rochester Hills, MI 48309

P 800 841 6279F 248 299 3884