
# ACOUSTIC CONNECT Cirrus

### **INSTALL GUIDE**

\*NOTE\* Assembly of multiple Systems shown





baresque.com.au

**e** info@baresque.com.au **p** 1300 306 399

#### MAKE SITE READY

#### Tips for Installation:

- 1. We recommend using a laser level for easy marking out and aligning systems
- 2. Check and count package components to be sure all parts are supplied before beginning
- 3. We would recommend a rendered print out of the layout to aid install
- 4. Check for low hanging services and lighting as the system will need to fit around or below these. Some site modification may be required on site by installer if obstruction present.

**Note:** this install guide is a recommendation only. Installer is responsible for site assessment to determine whether install guide is suiatable for the application

#### You Will Need:


- 1. Measuring tape
- 2. Pencil
- 3. Wide field laser level
- 4. Stanley Knife
- 5. Straight edge/Combination square
- 6. Ladder or work platform/scaffold
- 7. Drill and driver
- 8. Suitable countersunk screws for ceiling type
- 9. Highly recommend using a panel lifter for easy install

#### ASSEMBLY METHOD - CIRRUS

#### STEP 1

1) Interlock blades 1 and 2 as shown below. This will be a loose fit until step 2 is complete.


\*NOTE\* keep all male and female dovetail joints on the same side



#### STEP 2

2) Interlock blades 3-6 into assembly as shown. Slot will slide over intersection of blades 1 and 2. This will lock in any lateral movement.

\*NOTE\* again note direction of dovetail joins




#### **INSTALL METHOD**

#### STEP 3

3) Mark fixing points on ceiling starting from one corner of room as per layout below. Dimensions include allowance for end cappers. If offset from wall is specified, add this distance to first rows below. We would recommend leaving an offset/express gap of 10-20mm to minimise the impact of any bowing in the wall. This is not included in measurements below.

Continue with this until you reach terminating walls or assembly end.




TIP: A wide field laser level will help with marking out


## ACOUSTIC CONNECT Baresque INSTALL GUIDE

#### STEP 4

4) Consult the "Baresque Systems Fixing Directory", select the appropriate fixing method for your substrate & install 'hanger heads' to ceiling in marked locations.

Please note, screws are not supplied.





#### **INSTALL METHOD**

#### STEP 5

WIRE ADJUSTER

SWAGED WIRE •


**PUSH HERE** 

5) Feed swaged wire through tip of 'wire adjuster' (as shown). Push button (shown in grey) to adjust wire length. Release the button to lock in place.

#### STEP 6


6) Feed swaged wire through hole in the side of 'hanger head'. Screw 'wire adjuster' into 'hanger head', then adjust wires so they finish at the same length. Refer to specified height above floor level for this measurement.

## TIP: Be sure to include depth of blades in height measurement



#### STEP 7

7) Fit end cappers to dovetail joins that will be exposed or against walls






**INSTALL METHOD** 


#### STEP 8

8) Fit S-Hooks into precut slits in zintra profiles



#### STEP 9

9) Suspend assembly by looping 'S' hooks through swaged wire.



TIP: We recommend a panel lifter for lifting assembly safely and acurately




#### ASSEMBLY METHOD - CIRRUS 1A

#### STEP 10

10) Interlock blades 1 to 5 as shown below. This will be a loose fit until step 11 is complete.

\*NOTE\* part number 6 is an end piece which will fit onto adjacent system




#### STEP 11

11) Interlock blades 6-8 into assembly as shown. Slot will slide over intersection of blades 1 to 5. This will lock in any lateral movement.

Fit S-hooks into precut slit in Zintra profile

\*NOTE\* note direction of dovetail joins




**INSTALL METHOD** 

#### **STEP 12**

12) Suspend assembly by looping 'S' hooks through swaged wire.


Fit assembly to adjacent system installed in step 9. Locate dovetail joins and press fit together



#### **STEP 13**

13) Suspend next full assembly by looping 'S' hooks through swaged wire.

Fit assembly to adjacent system installed in step 9. Locate dovetail joins and press fit together






#### ASSEMBLY METHOD - CIRRUS 2A

#### **STEP 14**

14) Interlock blades 1 to 7 as shown below. This will be a loose fit until step 15 is complete.


\*NOTE\* direction of dovetail joins



#### **STEP 15**

15) Interlock blades 8-12 into assembly as shown. Slot will slide over intersection of blades 1 to 7. This will lock in any lateral movement.


Fit S-hooks into precut slit in Zintra profile



**INSTALL METHOD** 


#### STEP 16

16) Fit assembly to adjacent system installed in step 13. Locate dovetail joins and press fit together



#### **STEP 17**

17) Repeat steps 9 - 16 and install in both directions across room until meeting opposite walls or terminating system





INSTALL METHOD - SCRIBE TO WALL

#### **STEP 18**


18) Measure distance from end of installed system to terminating wall (or teminating location if not butting up against a wall).


Be sure to measure both ends of the system to be sure walls are square to assembly. We would recommend leaving an express gap of 10-20mm to minimise the impact of any bowing in the wall.

#### **STEP 19**

19) Mark distance on terminating assembly top edge. A laser will help to keep markings in a straight line.

\*NOTE\* measure and mark from shoulders of dovetail








**INSTALL METHOD** 


#### **STEP 20**

20) Using stanley knife and square / straight edge trim excess at marked point. A downward angle and pressure on the blade will make cutting easier.



#### **STEP 21**

21) Suspend corner terminating system.




INSTALL METHOD - SCRIBE TO WALL

#### **STEP 22**

22) Measure distance from end of installed system to terminating wall (or teminating location if not butting up against a wall).

Be sure to measure both ends of the system to be sure walls are square to assembly. We would recommend leaving an express gap of 10-20mm to minimise the impact of any bowing in the wall.




#### **STEP 23**

23) Mark distance on terminating assembly top edge. A laser will help to keep markings in a straight line.

Cut to size as per step 20.

\*NOTE\* Mark and measure from the shoulders of dovetail






**INSTALL METHOD** 


**STEP 24** 

24) Suspend middle terminating system



#### **STEP 25**

25) Repeat steps 23-23 and install all terminating systems until full ceiling is covered







#### **INSTALL METHOD**

#### **STEP 26**

26) Re-adjust wire length as explained in STEP 6 until entire assembly hangs level. Trim excess wire for a neat finish.











## ACOUSTIC CONNECT - CIRRUS

PARTS (PER SYSTEM)












## ACOUSTIC CONNECT - CIRRUS 1A

PARTS (PER SYSTEM)



1 OFF

1 OFF



## ACOUSTIC CONNECT - CIRRUS 2A

PARTS (PER SYSTEM)

