

## AGRIMAX FORTIS - Datenblatt



### Description

AGRIMAX FORTIS ist Ihr zuverlässiger Partner für alle Arbeiten im Bereich der Bodenvorbereitung und -bearbeitung sowie für den Transport. Zur Ausstattung hochmoderner und leistungsstarker Traktoren entwickelt, können Sie mit AGRIMAX FORTIS schwerste Lasten befördern und dabei Geschwindigkeiten von bis zu 65 km/h (40 mph) erreichen. Der Reifen bietet hervorragende Traktion neben ausgezeichnetem Handling und bestem Komfort für ein verbessertes Fahrerlebnis. Die verstärkte Nylonkarkasse maximiert Ihre Produktivität auf dem Feld und schützt den Boden durch reduzierte Bodenverdichtung.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>600/70 R 30</b>	SPECIAL	R1W	158 D/161 A8	DW 20 B	DW 18 L ; W 18 L	611	1602	724	4810	750	TL	E4-106R-001400
<b>600/70 R 30</b>	STANDARD	R1W	158 D/161 A8	DW 20 B	DW 18 L ; W 18 L	611	1602	724	4810	750	TL	E4-106R-001400
<b>600/70 R 34</b>	SPECIAL	R1W	160 D/163 A8	DW 18 L	DW 20 B ; W 18 L	591	1704	761	5109	800	TL	E4-106R-001401
<b>600/70 R 34</b>	STANDARD	R1W	160 D/163 A8	DW 18 L	DW 20 B ; W 18 L	591	1704	761	5109	800	TL	E4-106R-001401
<b>650/85 R 38</b>	SPECIAL	R1W	173 D/176 A8	DW 23 B	DW 21 B ; DW 20 B	675	2071	935	6184	975	TL	E4-106R-001426
<b>650/85 R 38</b>	STANDARD	R1W	173 D/176 A8	DW 23 B	DW 21 B ; DW 20 B	675	2071	935	6184	975	TL	E4-106R-001426
<b>800/70 R 38</b>	STANDARD	R1W	178 D/181 A8	DW 25 B	DW 27 B	798	2085	912	6202	975	TL	E4-106R-001424
<b>710/75 R 42</b>	SPECIAL	R1W	175 D/172 E	DW 23 B	DW 25 B	716	2133	970	6406	1000	TL	E4-106R-001835
<b>710/75 R 42</b>	STANDARD	R1W	175 D/172 E	DW 23 B	DW 25 B	716	2133	970	6406	1000	TL	E4-106R-001835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14.04.2025 08:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..