

## AGRIMAX RT 657 - Datenblatt



### Description

AGRIMAX RT 657 ist der ideale Reifen für die Bodenbearbeitung und den Einsatz auf der Straße; einige Größen sind auch zur Weinernte geeignet. Der Reifen bietet hervorragenden Fahrkomfort sowie deutliche Kraftstoffersparnis. Agrimax RT 657 ist die beste Wahl, für alle, die einen vielseitigen und zuverlässigen Reifen brauchen, ohne die Performance zu beeinträchtigen.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor • Traubenerntemaschine

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
320/65 R 16	STANDARD	R1W	117 D/120 A8	W 10	W 9 ; W 11	319	822	366	2466	390	TL		E4-106R-001815
320/65 R 18	STANDARD	R1W	109 A8/B	W 10	W 9 ; W 11	319	873	392	2587	425	TL		E4-106R-000636
320/65 R 18	STANDARD	R1W	125 A8/B	W 10	W 9 ; W 11	310	885	400	2667	400	TL		E11-106R-008145
340/65 R 18	STANDARD	R1W	113 A8/B	W 11	W 10 ; W 12	343	899	400	2667	425	TL		E4-106R-001816
340/65 R 20	STANDARD	R1W	124 D/127 A8	W 11	W 10 ; W 12	343	950	430	2892	450	TL		E4-106R-001413
420/65 R 20	STANDARD	R1W	135 D/138 A8	W 13	W 11 ; W 12	418	1054	468	3162	500	TL		E4-106R-001390
440/65 R 20	STANDARD	R1W	138 D/141 A8	W 14 L	W 13 ; W 15 L	441	1080	479	3240	525	TL		E4-106R-000760
420/65 R 24	STANDARD	R1W	138 D/141 A8	W 13	W 11 ; W 12	418	1156	519	3468	550	TL		E4-106R-000761
440/65 R 24	SPECIAL	R1W	135 D/138 A8	W 14 L	W 13 ; W 15 L	441	1182	538	3546	575	TL		E4-106R-000616
440/65 R 24	STANDARD	R1W	135 D/138 A8	W 14 L	W 13 ; W 15 L	441	1182	538	3546	575	TL		E4-106R-000616
480/65 R 24	SPECIAL	R1W	140 D/143 A8	W 15 L	W 14 L	479	1234	562	3730	600	TL	1	E4-106R-000617
480/65 R 24	STANDARD	R1W	140 D/143 A8	W 15 L	W 14 L	479	1234	562	3730	600	TL		E4-106R-000617
540/65 R 24	SPECIAL	R1W	146 D/149 A8	W 16 L	W 18 L	530	1312	590	3930	625	TL		E4-106R-000773
540/65 R 24	STANDARD	R1W	146 D/149 A8	W 16 L	W 18 L	530	1312	590	3930	625	TL		E4-106R-000773
420/65 R 28	STANDARD	R1W	135 D/138 A8	W 13	W 12 ; W 11	418	1257	584	3824	600	TL		E11-106R-002974
440/65 R 28	STANDARD	R1W	138 D/141 A8	W 14 L	W 13 ; W 15 L	441	1283	590	3927	625	TL		E4-106R-000767
480/65 R 28	STANDARD	R1W	142 D/145 A8	W 15 L	W 14 L	479	1335	610	4091	650	TL		E4-106R-000653
540/65 R 28	SPECIAL	R1W	149 D/152 A8	W 16 L	W 18 L	530	1413	643	4253	675	TL		E4-106R-000650
540/65 R 28	STANDARD	R1W	149 D/152 A8	W 16 L	W 18 L	530	1413	643	4253	675	TL		E4-106R-000650
600/65 R 28	SPECIAL	R1W	154 D/157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	TL		E4-106R-000621
600/65 R 28	STANDARD	R1W	154 D/157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	TL		E4-106R-000621
420/65 R 30	STANDARD	R1W	136 D/139 A8	W 13	W 12 ; W 11	418	1308	606	3952	625	TL		E11-106R-002975
540/65 R 30	SPECIAL	R1W	150 D/153 A8	W 16 L	W 18 L	530	1464	670	4403	700	TL		E4-106R-000651
540/65 R 30	STANDARD	R1W	150 D/153 A8	W 16 L	W 18 L	530	1464	670	4403	700	TL		E4-106R-000651
600/65 R 30	STANDARD	R1W	155 D/158 A8	DW 20 B	W 18 L	611	1542	697	4609	725	TL		E4-106R-001825
540/65 R 34	SPECIAL	R1W	152 D/155 A8	W 16 L	W 18 L	530	1566	712	4742	750	TL	1	E4-106R-000652
540/65 R 34	STANDARD	R1W	152 D/155 A8	W 16 L	W 18 L	530	1566	712	4742	750	TL		E4-106R-000652
600/65 R 34	SPECIAL	R1W	157 D/160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	TL	1	E4-106R-001405
600/65 R 34	STANDARD	R1W	157 D/160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	TL		E4-106R-001405
540/65 R	SPECIAL	R1W	153 D/156	W 16 L	W 18 L	530	1667	760	5059	800	TL	1	E4-106R-000589

38			A8									
<b>540/65 R 38</b>	STANDARD	R1W	153 D/156 A8	W 16 L	W 18 L	530	1667	760	5059	800	TL	E4-106R-000589
<b>600/65 R 38</b>	SPECIAL	R1W	159 D/162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	TL	E4-106R-000623
<b>600/65 R 38</b>	STANDARD	R1W	159 D/162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	TL	E4-106R-000623
<b>650/65 R 38</b>	SPECIAL	R1W	163 D/166 A8	DW 20 B	DW 21 B ; DW 23 B	645	1811	830	5483	875	TL	E4-106R-000624
<b>650/65 R 38</b>	STANDARD	R1W	163 D/166 A8	DW 20 B	DW 21 B ; DW 23 B	645	1811	830	5483	875	TL	E4-106R-000624
<b>650/65 R 38</b>	STEEL BELTED	R1W	178 A8/175 B	DW 20 B	DW 21 B ; DW 23 B	645	1816	827	5488	875	TL	E11-106R-008886
<b>900/55 R 38</b>	STANDARD	R1W	179 D/181 A8	DW 27 B	DW 30 B	880	1950	880	5842	925	TL	E11-106R-006946
<b>650/65 R 42</b>	STANDARD	R1W	165 D/168 A8	DW 20 B	DW 21 B ; DW 23 B	645	1913	878	5810	925	TL	E4-106R-000625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14.04.2025 09:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..