

580/70 R 38 155D TL TRAXION 70

EAN CODE: **8714692360817**
 SKU CODE: **LB58703855DT7LA00**
 ECE NUMBER: **E4-106R-004081**



Recommended rim width:	DW18L
Permitted rim width:	W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	595 mm
Outer Diameter:	1825 mm
Static Loaded Radius:	820 mm
Rolling Circumference:	5385 mm
SRI:	875
Tread depth:	56 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	3200	3630	4075	4510	4955	5305	5610	5950
10H	2655	3080	3500	3920	4210	4455		
25	2735	3175	3610	4040	4340	4590		
30	2655	3080	3500	3920	4210	4455		
40		2935	3335	3730	4010	4245		
50		2815	3200	3580	3845	4070		
65			3045	3410	3660	3875		
70			2770	3100	3330	3525		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.