

600/70 R 30 158D TL TRAXION XXL

EAN CODE: **8714692326967**
 SKU CODE: **LB60703058DTXLA00**
 ECE NUMBER: **E4-106R-001099**



Recommended rim width:	DW20B
Permitted rim width:	(D)W18L
Nominal Tyre Pressure:	240 kpa
Section Width:	630 mm
Outer Diameter:	1590 mm
Static Loaded Radius:	725 mm
Rolling Circumference:	4750 mm
SRI:	750
Tread depth:	53 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	3030	3440	3860	4275	4695	5030	5320	5635	5875	6075	6325	6375
10H	2515	2920	3320	3715	3990	4200	4455	4650	4815	4890		
25	2590	3010	3420	3825	4110	4325	4590	4790	4960	5035		
30	2515	2920	3320	3715	3990	4200	4455	4650	4815	4890		
40		2780	3160	3535	3800	3995	4245	4425	4585	4655		
50		2665	3030	3390	3640	3835	4070	4245	4395	4465		
65			2885	3230	3470	3650	3875	4045	4185	4250		
70			2625	2940	3155	3320	3525	3680	3810	3870		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.