

520/70 R 34 148D TL TRAXION 70

EAN CODE: **8714692360787**
 SKU CODE: **LB52703448DT7LA00**
 ECE NUMBER: **E4-106R-004051**



Recommended rim width:	DW16L
Permitted rim width:	(D)W15L/W16L/ (D)W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	525 mm
Outer Diameter:	1640 mm
Static Loaded Radius:	740 mm
Rolling Circumference:	4840 mm
SRI:	775
Tread depth:	54 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2570	2915	3275	3625	3980	4260	4505	4775
10H	2130	2475	2810	3145	3380	3620		
25	2195	2550	2900	3245	3485	3735		
30	2130	2475	2810	3145	3380	3620		
40		2355	2680	2995	3220	3450		
50		2260	2570	2875	3085	3310		
65			2445	2735	2940	3150		
70			2225	2490	2675	2865		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.