

# VF 750/60 R 30.5 IMP 187D TL FLOTATION OPTIMALL



EAN CODE: **8714692800573**  
SKU CODE: **LB75603087DFOLA00**  
ECE NUMBER: **E4-106R-004696**

Recommended rim width:	<b>AG 24.00</b>
Nominal Tyre Pressure:	<b>320 kpa</b>
Section Width:	<b>765 mm</b>
Outer Diameter:	<b>1680 mm</b>
Static Loaded Radius:	<b>735 mm</b>
Rolling Circumference:	<b>5060 mm</b>
SRI:	<b>800</b>
Tread depth:	<b>28 mm</b>

Speed (km/h)	Pressure (bar)						
	0,80	1,20	1,60	2,00	2,40	2,80	3,20
10	6315	8120	9830	11015	12710	14405	15990
25	5620	7225	8750	9805	11315	12825	14235
30	5430	6980	8455	9470	10925	12385	13750
40	4965	6385	7735	8665	9995	11330	12580
50	4505	5790	7015	7860	9065	10275	11410
65	3850	4950	5995	6715	7750	8785	9750
70	3505	4505	5455	6110	7050	7995	8875

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.