



GROWING TOGETHER

AGRIMAX SIRIO

fast speed radial tires



AGRIMAX SIRIO is the new high-speed tire (up to 70 km/h) developed by BKT for high-powered tractors. It has been designed to provide best performance both on the road and in the field. The high sidewall flexibility ensures an outstanding comfort to improve the driving experience.



HIGH SPEED



FIELD AND ROAD



HIGH LOAD CAPACITY



COMFORT



REINFORCED BEAD



STABILITY



FUEL ECONOMY



Name: AGRIMAX SIRIO - Radial Tire



540/65R30	150 D/147 E
IF600/70R30	165 D/162 E
540/65R34	152 D/149 E
540/65R38	153 D/150 E
710/70R38	171 D/168 E

High-powered Tractors



Technical features and user benefits:

■ **High-Speed performance**

AGRIMAX SIRIO is the new BKT high-speed tire specially designed for high-power tractors (over 250 HP). Thanks to its speed index E, AGRIMAX SIRIO allows to transport heavy loads up to 70 km/h.

■ **Less fuel, more productivity**

BKT is continuously engaged in the development of eco-friendly tires that have the smallest possible impact on our environment. AGRIMAX SIRIO fully meets this strict criterion: thanks to its always uniform footprint on the ground - especially on the road - the rolling resistance is significantly reduced. The result is a clear benefit for the farmer in terms of less fuel consumption.

■ **Excellent riding comfort**

The demand for excellent riding comfort has significantly increased among farmers. Since tractors and equipment are becoming always larger and heavier, a tire is required to provide a more enjoyable and accurate ride, reducing the signs of driver's fatigue as much as possible. Not least thanks to the excellent sidewall flexibility, AGRIMAX SIRIO offers outstanding comfort in any operating condition.

■ **Top stability**

Thanks to the special casing and its 6 polyester belts, the high-speed tire AGRIMAX SIRIO has an optimum footprint on the ground turning into best stability both on the road and in the field.

■ **Excellent heat dissipation**

The new sidewall compound and the enhanced bead drastically reduce the heat generated in the tire due to the particular stress at high speed.

AGRIMAX SIRIO

sizes available - metric system



SIZE	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	RIM		LOAD CAPACITY (KG/TIRE)								
						Standard	Alternative	↓								
30" 540/65 R 30 150 D/147 E	530	1464	669	4400	700	W 16 L	W 18	bar/ km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
								70	1450	1665	1910	2155	2400	2645	2860	3075
								65	1575	1810	2080	2345	2615	2885	3120	3350
								50	1655	1905	2185	2465	3750	3030	3275	3520
								40	1725	1985	2280	2570	2865	3160	3415	3670
								25	1870	2145	2465	2780	3100	3415	3695	3970
								10	2365	2715	3120	3520	3920	4325	4675	5025
IF 600/70 R 30 165 D/162 E	603	1602	713	4739	750	DW 21 B	DW 20 B	bar/ km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
								70	2235	2565	2945	3325	3705	4085	4420	4750
								65	2425	2785	3195	3605	4020	4430	4790	5150
								50	2425	2785	3195	3605	4020	4430	4790	5150
								40	2425	2785	3195	3605	4020	4430	4790	5150
								25	2425	2785	3195	3605	4020	4430	4790	5150
								10	2425	2785	3195	3605	4020	4430	4790	5150
34" 540/65 R 34 152 D/149 E	530	1566	721	4735	750	W 16 L	W 18	bar/ km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
								70	1530	1755	2015	2275	2535	2795	3025	3250
								65	1670	1920	2205	2485	2770	3055	3305	3550
								50	1755	2015	2315	2615	2910	3210	3470	3730
								40	1830	2105	2415	2725	3035	3350	3620	3890
								25	1980	2275	2615	2950	3285	3625	3920	4210
								10	2505	2880	3305	3730	4155	4580	4955	5325
38" 540/65 R 38 153 D/150 E	530	1667	769	5050	800	W 16 L	W 18 L	bar/ km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
								70	1575	1810	2080	2345	2615	2885	3120	3350
								65	1720	1975	2265	2555	2850	3140	3395	3650
								50	1805	2075	2380	2685	2995	3300	3570	3835
								40	1880	2160	2480	2800	3120	3440	3720	4000
								25	2040	2340	2685	3035	3380	3725	4030	4330
								10	2575	2960	3395	3835	4275	4710	5095	5475
710/70 R 38 171 D/168 E	716	1959	887	5917	925	DW 23 B	-	bar/ km/h	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
								70	2635	3025	3475	3920	4370	4820	5210	5600
								65	2895	3325	3815	4305	4800	5290	5720	6150
								50	3040	3490	4010	4525	5040	5560	6010	6460
								40	3170	3640	4180	4715	5255	5795	6265	6735
								25	3430	3940	4520	5105	5690	6270	6780	7290
								10	4340	4985	5720	6460	7200	7935	8580	9225

* ALL THE ABOVE TIRE SIZES ARE 'E' MARKED TIRES