

RT 857 - Datenblatt



Description

RT 857 ist ein Reifen der für die Bodenbearbeitung entwickelt wurde. Die robuste Karkasse bietet ausgezeichnete Beständigkeit und Traktionseigenschaften. Die gegenüber Stoppeln resistente Gummimischung der Lauffläche wartet mit hoher Schnitt- und Reißfestigkeit auf.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Traktor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
320/85 R 24 (12.4 R 24)	STANDARD	R1	122 A8/B	W 11	W 10 ; W 9	329	1154	528	3449	550	TL	E11-106R-002976
380/85 R 24 (14.9 R 24)	STANDARD	R1	131 A8/B	W 12	W 13 ; W 11	380	1256	566	3783	600	TL	E11-106R-002977
420/85 R 26 (16.9 R 26)	STANDARD	R1	138 A8/B	DW 15 L	W 14 L ; W 15 L ; W 16 L ; DW 16 L	450	1374	616	4115	650	TL	E11-106R-003471
460/85 R 26 (18.4 R 26)	STANDARD	R1	143 A8/B	DW 15 L	W 15 L ; W 16 L ; DW 16 L	465	1442	642	4297	675	TL	E4-106R-001479
320/85 R 28 (12.4 R 28)	STANDARD	R1	124 A8/B	W 11	W 9 ; W 10	329	1255	577	3779	600	TL	E4-106R-000757
340/85 R 28 (13.6 R 28)	STANDARD	R1	127 A8/B	W 12	W 11	353	1289	599	3908	625	TL	E4-106R-000759
380/85 R 28 (14.9 R 28)	STANDARD	R1	133 A8/B	W 12	W 11 ; W 13	390	1357	617	4127	650	TL	E4-106R-000769
420/85 R 28 (16.9 R 28)	STANDARD	R1	139 A8/B	W 15 L	W 14 L ; W 13	450	1425	640	4276	675	TL	E4-106R-000770
420/85 R 30 (16.9 R 30)	STANDARD	R1	140 A8/B	W 15 L	W 14 L ; W 13	450	1476	656	4398	700	TL	E4-106R-001394
460/85 R 30 (18.4 R 30)	STANDARD	R1	145 A8/B	W 16 L	W 15 L ; W 14 L	475	1544	697	4648	725	TL	E4-106R-001480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14.04.2025 12:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..