

340/80 R 18 IND143 A8/B TL TRAXION VERSA

EAN CODE: **8714692335341**
SKU CODE: **LB348018438TVLA00**
ECE NUMBER: **E4-106R-002527**



Alternative size:	335/80 R 18 12.5 R 18
Recommended rim width:	11
Permitted rim width:	W10/W11/11SDC/ 12/12SC
Nominal Tyre Pressure:	400 kpa
Section Width:	355 mm
Outer Diameter:	1000 mm
Static Loaded Radius:	455 mm
Rolling Circumference:	3000 mm
SRI:	475
Tread depth:	32 mm

Speed (km/h)	Pressure (bar)							
	1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40
0	2430	2970	3505	4045	4585	5150	5665	6265
10C	1585	1935	2285	2640	2990	3360	3695	4090
25	1370	1615	1865	2115	2375	2610	2890	
30	1340	1585	1830	2075	2330	2560	2835	
40	1290	1525	1760	1995	2240	2465	2725	
50	1290	1525	1760	1995	2240	2465	2725	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

400/70 R 20 IND 149A8/B TL TRAXION VERSA

EAN CODE: **8714692309922**
SKU CODE: **LB407020498TVLA00**
ECE NUMBER: **E4-106R-001117**



Alternative size: **405/70 R 20**
16.0/70 R 20

Recommended rim width:	13
Permitted rim width:	12SDC/13SDC/14
Nominal Tyre Pressure:	400 kpa
Section Width:	405 mm
Outer Diameter:	1075 mm
Static Loaded Radius:	475 mm
Rolling Circumference:	3250 mm
SRI:	525
Tread depth:	35 mm

Speed (km/h)	Pressure (bar)							
	1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40
0	2905	3550	4195	4840	5485	6095	6780	7475
10C	1895	2315	2735	3160	3580	3975	4420	4875
25	1635	1935	2230	2530	2810	3125	3445	
30	1605	1895	2190	2480	2755	3065	3380	
40	1545	1825	2105	2385	2650	2945	3250	
50	1545	1825	2105	2385	2650	2945	3250	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

400/70 R 24 IND 152A8/B TL TRAXION VERSA

EAN CODE: **8714692335358**
SKU CODE: **LB407024528TVLA00**
ECE NUMBER: **E4-106R-002530**



Alternative size:	405/70 R 24 16.0/70 R 24
Recommended rim width:	13
Permitted rim width:	12SDC/13SDC/14
Nominal Tyre Pressure:	400 kpa
Section Width:	405 mm
Outer Diameter:	1170 mm
Static Loaded Radius:	535 mm
Rolling Circumference:	3510 mm
SRI:	575
Tread depth:	35 mm

Speed (km/h)	Pressure (bar)							
	1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40
0	3150	3850	4550	5250	5950	6670	7350	8165
10C	2055	2510	2965	3425	3880	4350	4795	5325
25	1775	2095	2420	2740	3075	3385	3765	
30	1740	2055	2375	2690	3015	3325	3690	
40	1675	1980	2285	2585	2900	3195	3550	
50	1675	1980	2285	2585	2900	3195	3550	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

400/80 R 24 IND 162A8/B TL TRAXION VERSA

EAN CODE: **8714692335365**
SKU CODE: **LB408024628TVLA00**
ECE NUMBER: **E4-106R-002523**



Alternative size:	15.5/80 R 24
Recommended rim width:	DW13
Permitted rim width:	13
Nominal Tyre Pressure:	500 kpa
Section Width:	405 mm
Outer Diameter:	1240 mm
Static Loaded Radius:	570 mm
Rolling Circumference:	3740 mm
SRI:	600
Tread depth:	39 mm

Speed (km/h)	Pressure (bar)								
	1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40	5,00
0	3545	4335	5120	5910	6695	7475	8275	9200	10240
10C	2310	2825	3340	3855	4365	4875	5395	6000	6680
25	1995	2360	2725	3085	3445	3815	4240	4540	5035
30	1960	2315	2670	3030	3380	3740	4160	4455	4940
40	1885	2225	2570	2910	3250	3595	4000	4280	4750
50	1885	2225	2570	2910	3250	3595	4000	4280	4750

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

440/80 R 28 IND 156A8/B TL TRAXION VERSA

EAN CODE: **8714692336416**
SKU CODE: **LB448028568TVLA00**
ECE NUMBER: **E4-106R-002532**



Alternative size:	16.9 R 28
Recommended rim width:	DW14L
Permitted rim width:	DW15L
Nominal Tyre Pressure:	400 kpa
Section Width:	450 mm
Outer Diameter:	1415 mm
Static Loaded Radius:	640 mm
Rolling Circumference:	4270 mm
SRI:	675
Tread depth:	39 mm

Speed (km/h)	Pressure (bar)					
	1,60	2,00	2,40	2,80	3,20	3,60
0	4405	5380	6360	7340	8315	9200
10C	2870	3510	4150	4785	5425	6000
25	2480	2930	3380	3835	4240	
30	2435	2875	3320	3760	4160	
40	2340	2765	3190	3615	4000	
50	2340	2765	3190	3615	4000	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

460/70 R 24 IND 159A8/B TL TRAXION VERSA

EAN CODE: **8714692309946**
SKU CODE: **LB467024598TVLA00**
ECE NUMBER: **E4-106R-001117**



Alternative size:	17.5 LR 24
Recommended rim width:	DW15L
Permitted rim width:	DW14L/DW16L
Nominal Tyre Pressure:	400 kpa
Section Width:	480 mm
Outer Diameter:	1255 mm
Static Loaded Radius:	570 mm
Rolling Circumference:	3800 mm
SRI:	600
Tread depth:	38 mm

Speed (km/h)	Pressure (bar)							
	1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40
0	3915	4785	5655	6520	7390	8165	9130	10065
10C	2550	3120	3685	4255	4820	5325	5955	6565
25	2205	2605	3005	3405	3765	4210	4640	
30	2165	2555	2950	3340	3690	4130	4550	
40	2080	2460	2835	3215	3550	3970	4375	
50	2080	2460	2835	3215	3550	3970	4375	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

480/80 R 26 IND 160A8/B TL TRAXION VERSA

EAN CODE: **8714692309984**
SKU CODE: **LB488026608TVLA00**
ECE NUMBER: **E4-106R-001121**



Alternative size:	18.4 R 26
Recommended rim width:	DW15L
Permitted rim width:	DW16L
Nominal Tyre Pressure:	320 kpa
Section Width:	495 mm
Outer Diameter:	1440 mm
Static Loaded Radius:	645 mm
Rolling Circumference:	4320 mm
SRI:	675
Tread depth:	39 mm

Speed (km/h)	Pressure (bar)					
	1,60	2,00	2,40	2,80	3,20	3,60
0	4885	5970	7055	8145	9230	10350
10C	3185	3895	4605	5310	6020	6750
25	2750	3255	3755	4255	4770	
30	2700	3190	3680	4175	4680	
40	2595	3070	3540	4015	4500	
50	2595	3070	3540	4015	4500	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

500/70 R 24 IND 164A8/B TL TRAXION VERSA

EAN CODE: **8714692309960**
SKU CODE: **LB507024648TVLA00**
ECE NUMBER: **E4-106R-001119**



Alternative size:	19.5 LR 24
Recommended rim width:	DW16L
Permitted rim width:	DW15L/DW18L
Nominal Tyre Pressure:	400 kpa
Section Width:	515 mm
Outer Diameter:	1320 mm
Static Loaded Radius:	595 mm
Rolling Circumference:	4020 mm
SRI:	625
Tread depth:	39 mm

Speed (km/h)	Pressure (bar)							
	1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40
0	4460	5450	6445	7435	8425	9490	10410	11500
10C	2910	3555	4200	4850	5495	6190	6790	7500
25	2515	2970	3425	3885	4375	4795	5300	
30	2465	2915	3360	3810	4290	4705	5200	
40	2370	2800	3230	3665	4125	4525	5000	
50	2370	2800	3230	3665	4125	4525	5000	

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.