

# 320/65 R 16 117D TL TRAXION 65

EAN CODE: **8714692344688**  
 SKU CODE: **LB32651617DT6LA00**  
 ECE NUMBER: **E4-106R-003306**



Recommended rim width:	<b>W10</b>
Permitted rim width:	<b>W9/W11</b>
Nominal Tyre Pressure:	<b>240 kpa</b>
Section Width:	<b>320 mm</b>
Outer Diameter:	<b>825 mm</b>
Static Loaded Radius:	<b>370 mm</b>
Rolling Circumference:	<b>2455 mm</b>
SRI:	<b>390</b>
Tread depth:	<b>31 mm</b>

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	805	915	1030	1140	1250	1340	1415	1515	1640	1755	1855	1930
10H	670	775	885	990	1060	1120	1230	1330	1415	1480		
25	690	800	910	1020	1095	1155	1265	1375	1460	1525		
30	670	775	885	990	1060	1120	1230	1330	1415	1480		
40		740	840	940	1010	1070	1170	1270	1345	1405		
50		710	805	900	970	1025	1125	1215	1290	1350		
65			770	860	925	975	1070	1160	1230	1285		
70			700	780	840	885	975	1055	1120	1170		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.