

320/65 R 18 119D TL TRAXION 65

EAN CODE: **8714692344695**
 SKU CODE: **LB32651819DT6LA00**
 ECE NUMBER: **E4-106R-003307**



Recommended rim width:	W9
Permitted rim width:	W10/W11
Nominal Tyre Pressure:	240 kpa
Section Width:	310 mm
Outer Diameter:	875 mm
Static Loaded Radius:	390 mm
Rolling Circumference:	2605 mm
SRI:	425
Tread depth:	31 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	850	965	1085	1200	1320	1410	1490	1600	1725	1850	1955	2040
10H	705	820	930	1040	1120	1185	1295	1405	1490	1565		
25	725	845	960	1075	1155	1220	1335	1450	1535	1610		
30	705	820	930	1040	1120	1185	1295	1405	1490	1565		
40		780	885	990	1065	1130	1235	1340	1420	1490		
50		750	850	950	1020	1080	1185	1285	1360	1430		
65			810	905	975	1030	1130	1220	1295	1360		
70			735	825	885	935	1025	1110	1180	1240		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.