

340/65 R 18 122D TL TRAXION 65

EAN CODE: **8714692344732**
 SKU CODE: **LB34651822DT6LA00**
 ECE NUMBER: **E4-106R-003308**



Recommended rim width:	W9
Permitted rim width:	W10/W11
Nominal Tyre Pressure:	240 kpa
Section Width:	320 mm
Outer Diameter:	905 mm
Static Loaded Radius:	415 mm
Rolling Circumference:	2700 mm
SRI:	425
Tread depth:	33 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	935	1060	1190	1315	1445	1550	1640	1755	1895	2035	2145	2250
10H	775	900	1025	1145	1230	1325	1425	1545	1640	1725		
25	800	925	1055	1180	1265	1365	1470	1590	1690	1780		
30	775	900	1025	1145	1230	1325	1425	1545	1640	1725		
40		855	975	1090	1170	1260	1355	1470	1560	1645		
50		820	935	1045	1120	1210	1300	1410	1495	1575		
65			890	995	1070	1150	1240	1340	1425	1500		
70			810	905	975	1045	1125	1220	1295	1365		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.